automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 13/03/2023
	BRAKE FLUID DOT4	Printed on 31/03/2023
	(9204003-9204004-9204005-9204006)	Page n. 1/16
		Replaced revision:3 (Printed on: 11/11/2022)

Safety Data Sheet
According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the sub	stance	/mixture ar	nd of t	he com	pany/un	dertal	king	
1.1. Product identifier								
Product name	BRAKE	FLUID DOT4						
	· ·							
1.2. Relevant identified uses of the substance or	mixture ar	nd uses advise	d agains	it				
Intended use BRAKE FLUID DOT4			a againe					
	•							
Identified Uses	Industria	al		Profession	al		Consumer	
Functional Fluids								
1.3. Details of the supplier of the safety data shee								
Name		Service UK Lim						
Full address		ning Road, Was		0.007				
District and Country	ENGLA	ch, Worcesters	nire, B98	3 UDZ				
	Tel. +44	4 1527 838 300						
	Fax +44	4 1527 523 732						
e-mail address of the competent person								
responsible for the Safety Data Sheet	vsa.uk.	technical.maill	oox@val	eo.com				
1.4. Emergency telephone number								
For urgent inquiries refer to	(±44 15	27 838 300)(Bu	siness F	lours)				
Tor digent inquires refer to		nergency 24hrs		ioui o,				
		<u> </u>	<i>'</i>					
SECTION 2. Hazards identification								
2.1. Classification of the substance or mixture								
2.1. Classification of the substance of mixture								
The product is classified as hazardous pursuant to the								ndments an
supplements). The product thus requires a safety datas								
Any additional information concerning the risks for heal	th and/or t	the environment	are give	n in sectior	ns 11 and 12	of this	sheet.	
Hazard classification and indication:								
Reproductive toxicity, category 2		H361fd		Suspected	of damagin	a fertility	Suspected of dam:	aging the
reproductive toxicity, outegory 2		1100 Hu		Suspected of damaging fertility. Suspected of damaging the unborn child.				aging the
2.2. Label elements								
Hazard labelling pursuant to EC Regulation 1272/2008	(CLP) and	d subsequent ar	nendmer	its and sup	plements.			
					<u> </u>			
Hazard pictograms:				·				

automotive automotive	FTE AUTOMOTIVE	Revision nr. 4		
		Dated 13/03/2023		
	BRAKE FLUID DOT4	Printed on 31/03/2023 Page n. 2/16		
	(9204003-9204004-9204005-9204006)			
		Replaced revision:3 (Printed on: 11/11/2022)		

Signal words:	Warning

#### Hazard statements:

H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.

## Precautionary statements:

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
P102	Keep out of reach of children.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P101	If medical advice is needed, have product container or label at hand.
P405	Store locked up.
P201	Obtain special instructions before use.
Contains:	tris[2-[2-(2-methoxyethoxy]ethyl] borate

## 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage  $\geq$  than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration  $\geq$  0.1%.

# **SECTION 3. Composition/information on ingredients**

# 3.2. Mixtures

## Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)	
Reaction mass of 2-(2-(2- butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol			
CAS -	15 ≤ x < 20	Eye Dam. 1 H318	
EC 907-996-4		Eye Dam. 1 H318: ≥ 30%, Eye Irrit. 2 H319: ≥ 20%	
INDEX -			
REACH Reg. 01-2119475115-41- xxxx			
tris[2-[2-(2- methoxyethoxy)ethoxy]ethyl]			
<b>borate</b> CAS 30989-05-0	5 ≤ x < 10	Repr. 2 H361fd	
EC 250-418-4			
INDEX -			
REACH Reg. 01-2119462824-33- xxxx			
TRIETHYLENE GLYCOL			

automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 13/03/2023
	BRAKE FLUID DOT4	Printed on 31/03/2023
	(9204003-9204004-9204005-9204006)	Page n. 3/16
		Replaced revision:3 (Printed on: 11/11/2022)

CAS 112-27-6	5 ≤ x < 10	Substance with a community workplace exposure limit.	
EC 203-953-2			
INDEX -			
REACH Reg. 01-2119438366-35-			
XXXX			
2,6-di-tert-butyl-p-cresol			
CAS 128-37-0	$0.1 \le x < 0.2$	Aquatic Chronic 1 H410 M=1	
EC 204-881-4			
INDEX -			
REACH Reg. 01-2119480433-40-			
XXXX			

The full wording of hazard (H) phrases is given in section 16 of the sheet.

#### **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

# **SECTION 5. Firefighting measures**

# 5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

#### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

#### 5.3. Advice for firefighters

#### **GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 13/03/2023
	BRAKE FLUID DOT4	Printed on 31/03/2023
	(9204003-9204004-9204005-9204006)	Page n. 4/16
		Replaced revision:3 (Printed on: 11/11/2022)

# **SECTION 6. Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

# **SECTION 7. Handling and storage**

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

#### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

#### 7.3. Specific end use(s)

Information not available

# **SECTION 8. Exposure controls/personal protection**

#### 8.1. Control parameters

Regulatory References:

EU	OEL EU	Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

2-(2-(2-methoxyethoxy)ethoxy)ethanol								
Threshold Limit Value	Threshold Limit Value							
Туре	Country	TWA/8h		STEL/15min			Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm			
TLV-ACGIH		50						
Predicted no-effect concentration	Predicted no-effect concentration - PNEC							
Normal value in fresh water				10	10 mg/l			
Normal value in marine water				1	1 mg/l			
Normal value for fresh water sedin	36,6	36,6 mg/kg						
Normal value for marine water sec	diment			3,66		mg/kg		

automotive		Ī	TE AUTO	MOTIVE			Revi	sion nr. 4	
							Date	ed 13/03/2023	
		R	RAKE EL	UID DOT4			Prin	ted on 31/03/2023	
							Pag	e n. 5/16	
		(920400	3-9204004-	9204005-920	)4006)		ŭ	laced revision:3 (Prin	tod on: 11/11/2022
							Кер	laced revision.3 (Fill)	led on. 11/11/2022
Normal value for water, intermitte	nt release			50		mg/l			
Normal value of STP microorgani				200		mg/l			
Normal value for the food chain (s		ng)		89		mg/kg			
Normal value for the terrestrial co  Health - Derived no-effect le		MEI		1,56		mg/kg			
ricatii - Berived no-errect i	Effects on	1		T	Effects or	n			
	consumers				workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute loc		ute temic	Chronic local	Chronic systemic
Oral			VND	2 mg/kg					10 mg/kg
Inhalation	1	1	VND	02 mg/m2	1			VAID	bw/d
Inhalation Skin	+	+	VND VND	93 mg/m3 100 mg/kg	1	-		VND VND	156 mg/m3 167 mg/kg
				. 55 mg/kg					bw/d
Reaction mass of 2-(2-(2-but Predicted no-effect concentration		oxy)ethanol an	d 3,6,9,12-tetra	ioxahexadecai T	1-1-ol				
Normal value in fresh water	- PINEC			2		mg/l			
Normal value in marine water				0,2		mg/l			
Normal value for fresh water sedi				6,6		mg/kg			
Normal value for marine water se Normal value for water, intermitte				0,66 18		mg/kg mg/l			
Normal value of STP microorgani				500 mg/l					
Normal value for the food chain (s		ng)		333 mg/kg					
Normal value for the terrestrial co				0,46		mg/kg			
Health - Derived no-effect le	Effects on	MEL T			Effects or				
	consumers				workers	1			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute loc			Chronic local	Chronic
Oral				systemic 12,5 mg/kg		sys	temic		systemic
Oral				bw/d					
Inhalation				117 mg/m3					195 mg/m3
Skin				125 mg/kg bw/d					208 mg/kg bw/d
		1	1	bw/u	ı.	<u> </u>			DW/G
tris[2-[2-(2-methoxyethoxy)		orate							
Predicted no-effect concentration	- PNEC			0.011					
Normal value in fresh water  Normal value in marine water				0,211		mg/l mg/l			
Normal value for fresh water sedi	ment			0,76		mg/kg			
Normal value for marine water se	diment			0,076		mg/kg			
Normal value for water, intermittent release			2,112 mg/l						
,						ma/l			
Normal value of STP microorgani	sms			100		mg/l mg/ka			
,	sms mpartment	MEL				mg/l mg/kg			
Normal value of STP microorgani Normal value for the terrestrial co	sms mpartment evel - DNEL / DI Effects on	MEL		100	Effects or	mg/kg			
Normal value of STP microorgani Normal value for the terrestrial co Health - Derived no-effect le	sms smpartment evel - DNEL / DI Effects on consumers		Chronic local	100 0,028	workers	mg/kg	ıte	Chronic local	Chronic
Normal value of STP microorgani Normal value for the terrestrial co Health - Derived no-effect le Route of exposure	sms mpartment evel - DNEL / DI Effects on	MEL Acute systemic	Chronic local	100 0,028 Chronic systemic		mg/kg	ute temic	Chronic local	Chronic systemic
Normal value of STP microorgani Normal value for the terrestrial co Health - Derived no-effect le	sms smpartment evel - DNEL / DI Effects on consumers		Chronic local	100 0,028 Chronic	workers	mg/kg		Chronic local	
Normal value of STP microorgani Normal value for the terrestrial co Health - Derived no-effect le Route of exposure	sms smpartment evel - DNEL / DI Effects on consumers		Chronic local	100 0,028 Chronic systemic	workers	mg/kg		Chronic local	systemic
Normal value of STP microorgani Normal value for the terrestrial co Health - Derived no-effect le Route of exposure	sms smpartment evel - DNEL / DI Effects on consumers		Chronic local	100 0,028 Chronic systemic	workers	mg/kg		Chronic local	systemic
Normal value of STP microorgani Normal value for the terrestrial co Health - Derived no-effect le Route of exposure	sms smpartment evel - DNEL / DI Effects on consumers		Chronic local	100 0,028 Chronic systemic	workers	mg/kg	temic	/	systemic
Normal value of STP microorgani Normal value for the terrestrial co Health - Derived no-effect le  Route of exposure  Inhalation  TRIETHYLENE GLYCOL Threshold Limit Value	sms mpartment evel - DNEL / DI Effects on consumers Acute local	Acute systemic	Chronic local	Chronic systemic 7,2 mg/m3	workers	mg/kg	temic	/	systemic
Normal value of STP microorgani Normal value for the terrestrial co Health - Derived no-effect le Route of exposure Inhalation  TRIETHYLENE GLYCOL Threshold Limit Value	sms mpartment evel - DNEL / DI Effects on consumers Acute local	Acute systemic  TWA/8h		Chronic systemic 7,2 mg/m3	workers Acute loc	mg/kg	temic	/	systemic
Normal value of STP microorgani Normal value for the terrestrial co Health - Derived no-effect le  Route of exposure Inhalation  TRIETHYLENE GLYCOL Threshold Limit Value Type  OEL Predicted no-effect concentration	sms mpartment evel - DNEL / DI Effects on consumers Acute local  Country	Acute systemic  TWA/8h  mg/m3		Chronic systemic 7,2 mg/m3  STEL/15min mg/m3	workers Acute loc	mg/kg	temic	/	systemic
Normal value of STP microorgani Normal value for the terrestrial co Health - Derived no-effect le  Route of exposure Inhalation  TRIETHYLENE GLYCOL Threshold Limit Value Type  OEL Predicted no-effect concentration Normal value in fresh water	sms mpartment evel - DNEL / DI Effects on consumers Acute local  Country	Acute systemic  TWA/8h  mg/m3		Chronic systemic 7,2 mg/m3  STEL/15min mg/m3	workers Acute loc	mg/kg  al Acc sys	temic	/	systemic
Normal value of STP microorgani Normal value for the terrestrial co Health - Derived no-effect le  Route of exposure Inhalation  TRIETHYLENE GLYCOL Threshold Limit Value Type  OEL Predicted no-effect concentration Normal value in fresh water Normal value in marine water	sms mpartment evel - DNEL / DI Effects on consumers Acute local  Country  EU - PNEC	Acute systemic  TWA/8h  mg/m3		Chronic systemic 7,2 mg/m3  STEL/15min mg/m3	workers Acute loc	mg/kg  al Acc sys  mg/l  mg/l	temic	/	systemic
Normal value of STP microorgani Normal value for the terrestrial co Health - Derived no-effect le  Route of exposure Inhalation  TRIETHYLENE GLYCOL Threshold Limit Value Type  OEL Predicted no-effect concentration Normal value in fresh water	sms mpartment evel - DNEL / DI Effects on consumers Acute local  Country  EU - PNEC	Acute systemic  TWA/8h  mg/m3		Chronic systemic 7,2 mg/m3  STEL/15min mg/m3	workers Acute loc	mg/kg  al Acc sys	temic	/	systemic
Normal value of STP microorgani Normal value for the terrestrial co Health - Derived no-effect le  Route of exposure Inhalation  TRIETHYLENE GLYCOL Threshold Limit Value Type  OEL Predicted no-effect concentration Normal value in fresh water Normal value in marine water Normal value for fresh water sedi	mpartment  evel - DNEL / DI  Effects on consumers  Acute local  Country  EU - PNEC  ment sms impartment	Acute systemic  TWA/8h  mg/m3  1000		Chronic systemic 7,2 mg/m3  STEL/15min mg/m3	workers Acute loc	mg/kg  al Aci sys  mg/l mg/l mg/l mg/kg	temic	/	systemic

automotive automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 13/03/2023
	BRAKE FLUID DOT4	Printed on 31/03/2023
	(9204003-9204004-9204005-9204006)	Page n. 6/16
	· · · · · · · · · · · · · · · · · · ·	Replaced revision:3 (Printed on: 11/11/2022)

	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation			25 mg/m3	VND			50 mg/m3	VND
Skin			VND	20 mg/kg/d			VND	40 mg/kg/d

2,2'-metilimminodietai	nolo							
Predicted no-effect concen	tration - PNEC							
Normal value in fresh wate	r			0,1		mg/l		
Normal value in marine wa	ter			0,0125		mg/l		
Normal value for fresh water	er sediment			0,89		mg/kg		
Normal value for marine wa	ater sediment			0,111		mg/kg		
Normal value for water, intermittent release			1 mg/l		mg/l			
Normal value of STP micro	organisms			10 mg/l		mg/l		
Normal value for the terres	trial compartment			0,119		mg/kg		
Health - Derived no-ef	fect level - DNEL / D	MEL						
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute loca	l Acute systemic	Chronic loca	Chronic systemic
Inhalation								26 mg/m3
Skin								19 mg/kg

2,6-di-tert-butyl-p-cre	esol							
Threshold Limit Valu	е							
Туре	Country	TWA/8h		STEL/15min			Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm			
TLV-ACGIH		2						
Predicted no-effect conce	entration - PNEC							
Normal value in fresh wat	er			0,199	μg/l			
Normal value in marine w	ater			0,02	μg/l			
Normal value for fresh wa	ater sediment			99,6	99,6 μG/kg			
Normal value for marine v	water sediment			9,96	9,96 μG/kg			
Normal value for water, in	termittent release			1,99	1,99 µg/l			
Normal value of STP mici	roorganisms			0,17				
Normal value for the food	chain (secondary poiso	oning)		8,33	8,33 mg/kg			
Normal value for the terre	estrial compartment			47,69		μG/kg		
Health - Derived no-e	effect level - DNFI /	DMFI		•				

Health - Derived no-effect le	vei - DNEL / DIV	IEL						
	Effects on				Effects on			
	consumers				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		1 mg/kg bw/d		0,25 mg/kg bw/d				
Inhalation		3,1 mg/m3		0,78 mg/m3		18 mg/m3		4,4 mg/m3
Skin		6,7 mg/kg bw/d		1,7 mg/kg bw/d		19 mg/kg bw/d		4,7 mg/kg bw/d

METHYL-1H-BENZOTR	IAZOLE							
Predicted no-effect concentr	ation - PNEC							
Normal value in fresh water				0,008		mg/l		
Normal value in marine water	er			0,008		mg/l		
Normal value for fresh water	sediment			0,0025		mg/kg		
Normal value for marine wat	er sediment			0,0025		mg/kg		
Normal value for water, intermittent release				0,086	0,086 mg/l			
Normal value of STP microo	rganisms			39,4	mg/l			
Normal value for the terrestr	ial compartment			0,0024		mg/kg		
Health - Derived no-effe	ect level - DNEL / D	MEL						
	Effects on consumers				Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	0,25 mg/kg				

automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 13/03/2023
	BRAKE FLUID DOT4	Printed on 31/03/2023
	(9204003-9204004-9204005-9204006)	Page n. 7/16
		Replaced revision:3 (Printed on: 11/11/2022)

4,4 mg/m3

0,25 mg/kg

VND

VND

8,8 mg/m3

0,5 mg/kg

# Skin Legend:

Inhalation

(C) = CEILING: INHAL = Inhalable Fraction: RESP = Respirable Fraction: THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

VND

VND

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

# RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

#### **ENVIRONMENTAL EXPOSURE CONTROLS**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

# **SECTION 9. Physical and chemical properties**

## 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	colourless to amber	
Odour	characteristic	
Melting point / freezing point	Not available	
Initial boiling point	Not available	
Flammability	Not available	
Lower explosive limit	Not applicable	
Upper explosive limit	Not applicable	
Flash point	> 125 °C	
Auto-ignition temperature	~ 350 °C	

automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 13/03/2023
	BRAKE FLUID DOT4	Printed on 31/03/2023
	(9204003-9204004-9204005-9204006)	Page n. 8/16
		Replaced revision:3 (Printed on: 11/11/2022)

рН	8,9	
Kinematic viscosity	14,8 mm2/s	Temperature: 20 °C
Solubility	soluble in water	
Partition coefficient: n-octanol/water	Not available	
Vapour pressure	Not available	
Density and/or relative density	1,066 g/cm3	
Relative vapour density	Not available	
Particle characteristics	Not applicable	

## 9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU)	0	
VOC (volatile carbon)	0	

# **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

The product may react exothermically on contact with strong oxidising or reducing agents, strong acids or bases.

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Hygroscopic.

# 10.2. Chemical stability

Excessively high temperatures can cause thermal decomposition.

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Avoid exposure to: air.

Hygroscopic.

#### 10.3. Possibility of hazardous reactions

See paragraph 10.1.

#### 10.4. Conditions to avoid

Avoid overheating.

# 10.5. Incompatible materials

Oxidising or reducing agents. Strong acids or bases.

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Avoid contact with: strong acids, strong bases, water.

2,6-di-tert-butyl-p-cresol

Avoid contact with: oxidising agents.

## 10.6. Hazardous decomposition products

automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 13/03/2023
	BRAKE FLUID DOT4	Printed on 31/03/2023
	(9204003-9204004-9204005-9204006)	Page n. 9/16
		Replaced revision:3 (Printed on: 11/11/2022)

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Develops: carbon monoxide, carbon dioxide.

2,6-di-tert-butyl-p-cresol

In decomposition develops: carbon oxides.

# **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

**ACUTE TOXICITY** 

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	Not classified (no significant component)

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

LD50 (Dermal):	3540 mg/kg bw
LD50 (Oral):	5170 mg/kg bw

tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] borate

LD50 (Dermal):	> 2000 mg/kg
LD50 (Oral):	> 2000 mg/kg

automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 13/03/2023
	BRAKE FLUID DOT4	Printed on 31/03/2023
	(9204003-9204004-9204005-9204006)	Page n. 10/16
		Replaced revision:3 (Printed on: 11/11/2022)

#### TRIETHYLENE GLYCOL

LD50 (Dermal):	16 ml/kg bw
LD50 (Oral):	> 2000 mg/kg bw
LC50 (Inhalation vapours):	> 5,2 mg/l

## 2,6-di-tert-butyl-p-cresol

LD50 (Dermal):	> 2000 mg/kg dw
LD50 (Oral):	> 2930 mg/kg dw

# SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

#### SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

## RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

Respiratory sensitization

Information not available

Skin sensitization

Information not available

# GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

## CARCINOGENICITY

Does not meet the classification criteria for this hazard class

#### REPRODUCTIVE TOXICITY

Suspected of damaging fertility - Suspected of damaging the unborn child

## Adverse effects on sexual function and fertility

Information not available

automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 13/03/2023
	BRAKE FLUID DOT4	Printed on 31/03/2023
	(9204003-9204004-9204005-9204006)	Page n. 11/16
		Replaced revision:3 (Printed on: 11/11/2022)

Adverse effects on development of the offspring
Information not available
Effects on or via lactation
Information not available
STOT - SINGLE EXPOSURE
Does not meet the classification criteria for this hazard class
Target organs
Information not available
Route of exposure
Information not available
STOT - REPEATED EXPOSURE
Does not meet the classification criteria for this hazard class
Target organs
Information not available
Route of exposure

#### Route of exposure

Information not available

# ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

# 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

# **SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate

FTE	FTE AUTOMOTIVE	Revision nr. 4
automotive		
		Dated 13/03/2023
	BRAKE FLUID DOT4	Printed on 31/03/2023
	(9204003-9204004-9204005-9204006)	Page n. 12/16
		Replaced revision:3 (Printed on: 11/11/2022)
oil or vegetation.		
an robioty		
2,6-di-tert-butyl-p-cresol		
EC50 - for Crustacea	> 0,61 mg/l/48h	
Chronic NOEC for Crustacea	0,316 mg/l	

2,6-di-tert-butyl-p-cresol	
EC50 - for Crustacea	> 0,61 mg/l/48h
Chronic NOEC for Crustacea	0,316 mg/l
TRIETHYLENE GLYCOL	Lanca Wasi
LC50 - for Fish	69800 mg/l/96h
EC50 - for Crustacea	> 10000 mg/l/48h
Reaction mass of 2-(2-(2-	
butoxyethoxy)ethoxy)ethanol and 3,6,9,12-	
tetraoxahexadecan-1-ol	
LC50 - for Fish	> 1800 mg/l/96h
EC50 - for Crustacea	> 3200 mg/l/48h
EC50 - for Algae / Aquatic Plants	391 mg/l/72h
EC10 for Algae / Aquatic Plants	188 mg/l/72h
tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl]	
borate	000 0
LC50 - for Fish	> 222,2 mg/l/96h
EC50 - for Crustacea	> 211,2 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 224,4 mg/l/72h
2,6-di-tert-butyl-p-cresol NOT rapidly degradable	
TRIETHYLENE GLYCOL	
Rapidly degradable	
tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl]	
borate	
Rapidly degradable 12.3. Bioaccumulative potential	
TRIETHYLENE GLYCOL	
TRIETHYLENE GLYCOL Partition coefficient: n-octanol/water	-1,75
Partition coefficient: n-octanol/water  Reaction mass of 2-(2-(2-	-1,75
Partition coefficient: n-octanol/water  Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-	-1,75
Partition coefficient: n-octanol/water  Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol	
Partition coefficient: n-octanol/water  Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Partition coefficient: n-octanol/water	0,51
Partition coefficient: n-octanol/water  Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol	
Partition coefficient: n-octanol/water  Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Partition coefficient: n-octanol/water	
Partition coefficient: n-octanol/water  Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Partition coefficient: n-octanol/water  12.4. Mobility in soil	
Partition coefficient: n-octanol/water  Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Partition coefficient: n-octanol/water  12.4. Mobility in soil  TRIETHYLENE GLYCOL Partition coefficient: soil/water	0,51
Partition coefficient: n-octanol/water  Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Partition coefficient: n-octanol/water  12.4. Mobility in soil  TRIETHYLENE GLYCOL	0,51

automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 13/03/2023
	BRAKE FLUID DOT4	Printed on 31/03/2023
	(9204003-9204004-9204005-9204006)	Page n. 13/16
		Replaced revision:3 (Printed on: 11/11/2022)

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

#### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

# **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

#### 14.1. UN number or ID number

Not applicable

14.2. UN proper shipping name

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 13/03/2023
	BRAKE FLUID DOT4	Printed on 31/03/2023
	(9204003-9204004-9204005-9204006)	Page n. 14/16
		Replaced revision:3 (Printed on: 11/11/2022)

Not applicable

## 14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

# **SECTION 15. Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>		
Point	3	

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

Not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

## 15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] borate

TRIETHYLENE GLYCOL

2,6-di-tert-butyl-p-cresol

automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 13/03/2023
	BRAKE FLUID DOT4	Printed on 31/03/2023
	(9204003-9204004-9204005-9204006)	Page n. 15/16
		Replaced revision:3 (Printed on: 11/11/2022)

# **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Repr. 2	Reproductive toxicity, category 2	
Eye Dam. 1	Serious eye damage, category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1	
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.	
H318	Causes serious eye damage.	
H410	Very toxic to aquatic life with long lasting effects.	

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

## **GENERAL BIBLIOGRAPHY**

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 944/2013 (IV Atp. CLP) of the European Parliament 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)

automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 13/03/2023
	BRAKE FLUID DOT4	Printed on 31/03/2023
	(9204003-9204004-9204005-9204006)	Page n. 16/16
		Replaced revision:3 (Printed on: 11/11/2022)

- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

msds for B2C.

Changes to previous review: The following sections were modified: 02 / 03 / 09 / 11 / 16.