au to motive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 31/03/2023
		Batea 6 1766/2020
	BRAKE FLUID DOT 4 PLUS	Printed on 31/03/2023
	(9204007-9204008)	Page n. 1/18
		Replaced revision:3 (Printed on: 14/11/2022)

Safety Data Sheet

According to Annex II to REACH - Regulation 2020/878 and to Annex II to UK REACH

1.1. Product identifier					
Product name		BRAKE FLUID DOT 4 PLUS			
		!			
1.2. Relevant identified uses	s of the substance or n	nixture and uses advised	against		
Intended use	BRAKE FLUID DOT 4				
	Į.				
Identified Uses		Industrial	Professional	Consumer	
Functional Fluids					
		•	•	•	
1.3. Details of the supplier of	of the safety data sheet				
Name		Valeo Service UK Limited			
Full address		53 Heming Road, Washford			
District and Country		Redditch, Worcestershire, B98 0DZ			
		ENGLAND			
		Tel. +44 1527 838 300			
		Fax +44 1527 523 732			
e-mail address of the compet	ent person				
responsible for the Safety Data Sheet		vsa.uk.technical.mailbox@valeo.com			
1.4. Emergency telephone r	number				
For urgent inquiries refer to		(+44 1527 838 300)(Busi 999 (emergency 24hrs)	ness Hours)		

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Reproductive toxicity, category 2	H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.

automotive automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 31/03/2023
	BRAKE FLUID DOT 4 PLUS	Printed on 31/03/2023
	(9204007-9204008)	Page n. 2/18
		Replaced revision:3 (Printed on: 14/11/2022)

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:				

Signal words:	Warning

Hazard statements:

H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.
--------	--

Precautionary statements:

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
P102	Keep out of reach of children.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P101	If medical advice is needed, have product container or label at hand.
P405	Store locked up.
P201	Obtain special instructions before use.
Contains:	tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] borate

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\geq 0.1\%$.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)	

a u t o m o t i v e	FTE AUTOMOTIVE	Revision nr. 4
		Dated 31/03/2023
	BRAKE FLUID DOT 4 PLUS	Printed on 31/03/2023
	(9204007-9204008)	Page n. 3/18
		Replaced revision:3 (Printed on: 14/11/2022)

tris[2-[2-(2-methoxyethoxy)ethoxy] ethyl] borate			
CAS 30989-05-0	60 ≤ x < 70	Repr. 2 H361fd	
EC 250-418-4			
INDEX -			
REACH Reg. 01-2119462824-33-xxxx			
DI-ISOPROPANOLAMINE			
CAS 110-97-4	1 ≤ x < 3	Eye Irrit. 2 H319	
EC 203-820-9			
INDEX 603-083-00-7			
REACH Reg. 01-2119475444-34-xxxx			
Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethan ol and 3,6,9,12-tetraoxahexadecan-1-ol			
CAS -	1≤x< 3	Eye Dam. 1 H318	
EC 907-996-4		Eye Dam. 1 H318: ≥ 30%, Eye Irrit. 2 H319: ≥ 20%	
INDEX -			
REACH Reg. 01-2119475115-41-xxxx			
2,6-di-tert-butyl-p-cresol			
CAS 128-37-0	0,1 ≤ x < 0,2	Aquatic Chronic 1 H410 M=1	
EC 204-881-4			
INDEX -			
REACH Reg. 01-2119480433-40-xxxx			

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

automotive automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 31/03/2023
	BRAKE FLUID DOT 4 PLUS	Printed on 31/03/2023
	(9204007-9204008)	Page n. 4/18
		Replaced revision:3 (Printed on: 14/11/2022)

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not

FTE automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 31/03/2023
	BRAKE FLUID DOT 4 PLUS	Printed on 31/03/2023
	(9204007-9204008)	Page n. 5/18
		Replaced revision:3 (Printed on: 14/11/2022)

eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

TLV-ACGIH ACGIH 2021

Predicted no-effect concent	ration - PNEC			0.211						
Normal value in fresh water						mg/l				
Normal value in marine water						mg/l				
Normal value for fresh wate	0,76		mg/k	g						
Normal value for marine water sediment					·	mg/kg				
Normal value for water, inte	rmittent release			2,112	mg/l		ng/l			
Normal value of STP micro	organisms			100	mg/l					
Normal value for the terrest	rial compartment			0,028	0,028 mg		mg/kg			
Health - Derived no-eff	ect level - DNEL / D	MEL								
	Effects on consumers				Effects on workers					
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute loca		Acute systemic	Chror	nic local	Chronic systemic
Inhalation				7,2 mg/m3						29,1 mg/m3

2-(2-(2-methoxyethoxy)ethoxy)ethanol									
Threshold Limit Value									
Туре	Country	TWA/8h		STEL/15min			Remarks / Observations		
		mg/m3	ppm	mg/m3	ppm				
TLV-ACGIH		50							
Predicted no-effect cond	centration - PNEC								
Normal value in fresh w	rater			10	mg/l				
Normal value in marine	water			1	1 mg/				
Normal value for fresh v	water sediment			36,6		mg/kg			
			3,66	3,66					
Normal value for water,	intermittent release			50	50 mg/l				

automotive automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 31/03/2023
	BRAKE FLUID DOT 4 PLUS	Printed on 31/03/2023
	(9204007-9204008)	Page n. 6/18
		Replaced revision:3 (Printed on: 14/11/2022)

Normal value of STP microorgar	ormal value of STP microorganisms					mg/l				
Normal value for the food chain (secondary poisoning)					89		mg/kg			
Normal value for the terrestrial compartment				1,56	1,56 m		mg/kg			
Health - Derived no-effect level - DNEL / DMEL										
	Effects on consumers				Effects or workers	1				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute loca		Acute systemic	Chro	onic local	Chronic systemic
Oral			VND	2 mg/kg						10 mg/kg bw/d
Inhalation			VND	93 mg/m3				VNE)	156 mg/m3
Skin			VND	100 mg/kg				VNE)	167 mg/kg bw/d

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol										
Predicted no-effect concentration	- PNEC									
Normal value in fresh water				2	2 mg/l					
Normal value in marine water	0,2	0,2								
Normal value for fresh water sedi	6,6		mg/k	g						
Normal value for marine water sediment						mg/k	g			
Normal value for water, intermittent release						mg/l				
Normal value of STP microorgani	Normal value of STP microorganisms					mg/l				
Normal value for the food chain (s	Normal value for the food chain (secondary poisoning)					mg/kg		mg/kg		
Normal value for the terrestrial co	mpartment			0,46	0,46		mg/kg			
Health - Derived no-effect le	evel - DNEL / DI	MEL								
	Effects on consumers				Effects or workers	n				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute loc	al	Acute systemic	Chr	onic local	Chronic systemic
Oral				12,5 mg/kg bw/d						
Inhalation				117 mg/m3						195 mg/m3
Skin				125 mg/kg bw/d						208 mg/kg bw/d

2,6-di-tert-butyl-p-cresol										
Threshold Limit Value										
Туре	Country	TWA/8h		STEL/15min			Remarks / Observations			
		mg/m3	ppm	mg/m3	ppm					
TLV-ACGIH		2								
Predicted no-effect cond	centration - PNEC									
Normal value in fresh wa	ater			0,199	0,199 μg/l					
Normal value in marine	water			0,02	0,02 μg/l					
Normal value for fresh w	vater sediment			99,6	99,6					
Normal value for marine water sediment			9,96	9,96						
Normal value for water,	intermittent release			1,99	1,99 μg/l					

automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 31/03/2023
	BRAKE FLUID DOT 4 PLUS	Printed on 31/03/2023
	(9204007-9204008)	Page n. 7/18
		Replaced revision:3 (Printed on: 14/11/2022)

Normal value of STP microor	Normal value of STP microorganisms					mg/l				
Normal value for the food chain (secondary poisoning)				8,33 r		mg/k	g			
Normal value for the terrestrial compartment			47,69		μG/k	μG/kg				
Health - Derived no-effect level - DNEL / DMEL										
	Effects on consumers				Effects or workers	1				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute loca		Acute systemic	Chro	nic local	Chronic systemic
Oral		1 mg/kg bw/d		0,25 mg/kg bw/d						
Inhalation		3,1 mg/m3		0,78 mg/m3			18 mg/m3			4,4 mg/m3
Skin		6,7 mg/kg bw/d		1,7 mg/kg bw/d			19 mg/kg bw/d			4,7 mg/kg bw/d

METHYL-1H-BENZOTR	IAZOLE									
Predicted no-effect concentre	ation - PNEC									
Normal value in fresh water				0,008	08 mg/l					
Normal value in marine wate	0,008		mg/l							
Normal value for fresh water sediment						mg/kg	9			
Normal value for marine water sediment						mg/kg	9			
Normal value for water, intermittent release				0,086		mg/l				
Normal value of STP microorganisms				39,4	mg/		mg/l			
Normal value for the terrestri	ial compartment			0,0024	m		mg/kg			
Health - Derived no-effe	ect level - DNEL / D	MEL								
	Effects on consumers				Effects or workers	١				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute loc		Acute systemic	Chro	onic local	Chronic systemic
Oral			VND	0,25 mg/kg						
Inhalation			VND	4,4 mg/m3				VNE)	8,8 mg/m3
Skin			VND	0,25 mg/kg				VNE)	0,5 mg/kg

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

FTE automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 31/03/2023
	BRAKE FLUID DOT 4 PLUS	Printed on 31/03/2023
	(9204007-9204008)	Page n. 8/18
		Replaced revision:3 (Printed on: 14/11/2022)

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	
Colour	colourless to amber	
Odour	characteristic	
Melting point / freezing point	Not available	
Initial boiling point	> 265 °C	
Flammability	not applicable	
Lower explosive limit	Not applicable	
Upper explosive limit	Not applicable	
Flash point	> 125 °C	
Auto-ignition temperature	~ 350 °C	
рН	7-11	
Kinematic viscosity	Not available	
Solubility	soluble	
Partition coefficient: n-octanol/water	Not available	
Vapour pressure	Not available	
Density and/or relative density	1,065 g/cm3	
Relative vapour density	Not available	

FTE automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 31/03/2023
	BRAKE FLUID DOT 4 PLUS	Printed on 31/03/2023
	(9204007-9204008)	Page n. 9/18
		Replaced revision:3 (Printed on: 14/11/2022)

				_
Particle characteristics	Not applicable			
		-		
9.2. Other information				
9.2.1. Information with regard to phy	vsical hazard classes			
Information not available				
9.2.2. Other safety characteristics				
VOC (Directive 2010/75/EU)	0			

SECTION 10. Stability and reactivity

10.1. Reactivity

The product may react exothermically on contact with strong oxidising or reducing agents, strong acids or bases.

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Hygroscopic.

10.2. Chemical stability

Excessively high temperatures can cause thermal decomposition.

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Avoid exposure to: air.

Hygroscopic.

10.3. Possibility of hazardous reactions

See paragraph 10.1.

10.4. Conditions to avoid

Avoid overheating.

10.5. Incompatible materials

Oxidising or reducing agents. Strong acids or bases.

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Avoid contact with: strong acids, strong bases, water.

2,6-di-tert-butyl-p-cresol

Avoid contact with: oxidising agents.

10.6. Hazardous decomposition products

automotive automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 31/03/2023
	BRAKE FLUID DOT 4 PLUS	Printed on 31/03/2023
	(9204007-9204008)	Page n. 10/18
		Replaced revision:3 (Printed on: 14/11/2022)

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Develops: carbon monoxide, carbon dioxide.

2,6-di-tert-butyl-p-cresol

In decomposition develops: carbon oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:	Not classified (no significant component)
ATE (Oral) of the mixture:	Not classified (no significant component)
ATE (Dermal) of the mixture:	Not classified (no significant component)

tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] borate

LD50 (Dermal):	> 2000 mg/kg
----------------	--------------

FTE automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 31/03/2023
	BRAKE FLUID DOT 4 PLUS	Printed on 31/03/2023
	(9204007-9204008)	Page n. 11/18
		Replaced revision:3 (Printed on: 14/11/2022)

LD50 (Oral):	> 2000 mg/kg
== 0 0 (0 1 0 1)	

DI-ISOPROPANOLAMINE

LD50 (Oral):	6720 mg/kg
LD30 (Olai).	

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

LD50 (Dermal):	3540 mg/kg bw
LD50 (Oral):	5170 mg/kg bw

2,6-di-tert-butyl-p-cresol

LD50 (Dermal):	> 2000 mg/kg dw
LD50 (Oral):	> 2930 mg/kg dw

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

Serious eye damage/eye irritation

Product:

Species: Bovine cornea Assessment: No eye irritation Method: OECD Test Guideline 437

Result: No eye irritation

GLP: yes

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

Respiratory sensitization

Information not available

Skin sensitization

Information not available

GERM CELL MUTAGENICITY

FTE automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 31/03/2023
	BRAKE FLUID DOT 4 PLUS	Printed on 31/03/2023
	(9204007-9204008)	Page n. 12/18
		Replaced revision:3 (Printed on: 14/11/2022)

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Suspected of damaging fertility - Suspected of damaging the unborn child

Adverse effects on sexual function and fertility

Information not available

Adverse effects on development of the offspring

Information not available

Effects on or via lactation

Information not available

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

Information not available

Route of exposure

Information not available

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

Target organs

automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 31/03/2023
	BRAKE FLUID DOT 4 PLUS	Printed on 31/03/2023
	(9204007-9204008)	Page n. 13/18
		Replaced revision:3 (Printed on: 14/11/2022)

Information not available

Route of exposure

Information not available

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

2,6-di-tert-butyl-p-cresol	
EC50 - for Crustacea	> 0,61 mg/l/48h
Chronic NOEC for Crustacea	0,316 mg/l
DI-ISOPROPANOLAMINE	
LC50 - for Fish	> 222,2 mg/l/96h
Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol	
LC50 - for Fish	> 1800 mg/l/96h
EC50 - for Crustacea	> 3200 mg/l/48h
EC50 - for Algae / Aquatic Plants	391 mg/l/72h
EC10 for Algae / Aquatic Plants	188 mg/l/72h
tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] borate	
LC50 - for Fish	> 222,2 mg/l/96h
EC50 - for Crustacea	> 211,2 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 224,4 mg/l/72h

FTE automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 31/03/2023
	BRAKE FLUID DOT 4 PLUS	Printed on 31/03/2023
	(9204007-9204008)	Page n. 14/18
		Replaced revision:3 (Printed on: 14/11/2022)

12.2. Persistence and degradability

2,6-di-tert-butyl-p-cresol	
NOT rapidly degradable	
DI-ISOPROPANOLAMINE	
Rapidly degradable	
tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] borate	
Rapidly degradable 12.3. Bioaccumulative potential	
Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol	
2-(2-(2-butoxyethoxy)ethoxy)ethanol and	0,51
2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol	0,51
2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol Partition coefficient: n-octanol/water	0,51

0,008

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Partition coefficient: soil/water

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

automotive automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 31/03/2023
	BRAKE FLUID DOT 4 PLUS	Printed on 31/03/2023
	(9204007-9204008)	Page n. 15/18
		Replaced revision:3 (Printed on: 14/11/2022)

	(9204007-9204008)	Page n. 15/18
	(Replaced revision:3 (Printed on: 14/11/2022)
	current provisions of the Code of International Carriage of Dangerou Goods Code (IMDG), and of the International Air Transport Association	
14.1. UN number or ID number		() 3
Not applicable		
14.2. UN proper shipping name		
Not applicable		
14.3. Transport hazard class(es)		
Not applicable		
14.4. Packing group		
Not applicable		
That applicable		
14.5. Environmental hazards		
Not applicable		
Not applicable		
14.6. Special precautions for user		
Not applicable		
14.7. Maritime transport in bulk acco	ording to IMO instruments	
Information not relevant		
SECTION 15. Regulatory	information	
15.1. Safety, health and environme	ental regulations/legislation specific for the substance or mixture	Đ
Seveso Category - Directive 2012/18/E	EU: None	

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

<u>Product</u>		
Point	3	

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

FTE automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 31/03/2023
	BRAKE FLUID DOT 4 PLUS	Printed on 31/03/2023
	(9204007-9204008)	Page n. 16/18
		Replaced revision:3 (Printed on: 14/11/2022)

Not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] borate

DI-ISOPROPANOLAMINE

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

2,6-di-tert-butyl-p-cresol

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Repr. 2	Reproductive toxicity, category 2	
Eye Dam. 1	Serious eye damage, category 1	
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1	
H361fd	Suspected of damaging fertility. Suspected of damaging the unborn child.	
H318	Causes serious eye damage.	
H410	Very toxic to aquatic life with long lasting effects.	

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate

automotive automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 31/03/2023
	BRAKE FLUID DOT 4 PLUS	Printed on 31/03/2023
	(9204007-9204008)	Page n. 17/18
		Replaced revision:3 (Printed on: 14/11/2022)

- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

FTE automotive	FTE AUTOMOTIVE	Revision nr. 4
		Dated 31/03/2023
	BRAKE FLUID DOT 4 PLUS	Printed on 31/03/2023
	(9204007-9204008)	Page n. 18/18
		Replaced revision:3 (Printed on: 14/11/2022)

Note for users

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

msds for B2C.

Changes to previous review: The following sections were modified: 02 / 03 / 08 / 09 / 11 / 16.