

# **VALEO BRAKE AND CLUTCH FLUID DOT 3**

Revision nr. 4

Dated 04/08/2025

Printed on 04/08/2025

Page n. 1/18

Replaced revision:3 (Printed on: 14/11/2022)

# Safety Data Sheet According to Annex II to REACH - Regulation (EU) 2020/878

# SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

VALEO BRAKE AND CLUTCH FLUID DOT 3 Product name

UFI: 25F0-U0K0-D00P-6UQY

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **BRAKE FLUID DOT 3 (for B2C)** 

	Identified Uses	Industrial	Professional	Consumer				
	Functional Fluids	₩	✓	✓				
	1.3. Details of the supplier of the safety data sheet							
Name		Valeo Service Middle-East						
	Full address	Avdınevler Mahallesi, Sanavi Caddesi.						

District and Country ETS Plaza No:32 Kat:7 Maltepe Istanbul 34854 - Istanbul

Turkey

Tel. +90 (216) 587 70 00

e-mail address of the competent person

responsible for the Safety Data Sheet alert.middle-east@valeo.com

1.4. Emergency telephone number

For urgent inquiries refer to EG: 123 QA: 999 **UAE: 998** 

LB: 140

### **SECTION 2. Hazards identification**

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Acute toxicity, category 4 H302 Harmful if swallowed. Serious eye damage, category 1 H318 Causes serious eye damage.

# 2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



# **VALEO BRAKE AND CLUTCH FLUID DOT 3**

Revision nr. 4

Dated 04/08/2025

Printed on 04/08/2025

Page n. 2/18

Replaced revision:3 (Printed on: 14/11/2022)

#### Hazard pictograms:





Signal words: Danger

Hazard statements:

H302 Harmful if swallowed.

H318 Causes serious eye damage.

Precautionary statements:

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

P102 Keep out of reach of children.

P101 If medical advice is needed, have product container or label at hand.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsing.

P280 Wear eye protection / face protection.

P310 Immediately call a POISON CENTER / doctor / . . .

Contains: Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

DIETHYLENE GLYCOL

#### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

# **SECTION 3. Composition/information on ingredients**

#### 3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

INDEX -  $45 \le x < 70$  Eye Dam. 1 H318

EC 907-996-4 Eye Dam. 1 H318: ≥ 30%, Eye Irrit. 2 H319: ≥ 20% - < 30%



# **VALEO BRAKE AND CLUTCH FLUID DOT 3**

Revision nr. 4

Dated 04/08/2025

Printed on 04/08/2025

Page n. 3/18

Replaced revision:3 (Printed on: 14/11/2022)

CAS -

REACH Reg. 01-2119475115-41-

xxxx

DIETHYLENE GLYCOL

INDEX 603-140-00-6  $10 \le x < 30$  Acute Tox. 4 H302 EC 203-872-2 ATE Oral: 500 mg/kg

CAS 111-46-6

REACH Reg. 01-2119457857-21-

xxxx

TRIETHYLENE GLYCOL

INDEX -  $5 \le x < 10$  Substance with a community workplace exposure limit.

EC 203-953-2 CAS 112-27-6

REACH Reg. 01-2119438366-35-

XXXX

2,6-di-tert-butyl-p-cresol

INDEX -  $0.1 \le x < 0.2$  Aquatic Chronic 1 H410 M=1

EC 204-881-4 CAS 128-37-0

REACH Reg. 01-2119480433-40-

XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

### **SECTION 4. First aid measures**

#### 4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. Get medical advice/attention.

# Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

#### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Immediately call a POISON CENTER / doctor / . . .



# **VALEO BRAKE AND CLUTCH FLUID DOT 3**

Revision nr. 4

Dated 04/08/2025

Printed on 04/08/2025

Page n. 4/18

Replaced revision:3 (Printed on: 14/11/2022)

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

### **SECTION 5. Firefighting measures**

#### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

#### 5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

#### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

### **SECTION 6. Accidental release measures**

# 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

#### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

#### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

#### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

### **SECTION 7. Handling and storage**



# **VALEO BRAKE AND CLUTCH FLUID DOT 3**

Revision nr. 4

Dated 04/08/2025

Printed on 04/08/2025

Page n. 5/18

Replaced revision:3 (Printed on: 14/11/2022)

#### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

# 7.3. Specific end use(s)

Information not available

# **SECTION 8. Exposure controls/personal protection**

### 8.1. Control parameters

Regulatory references:

DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoiu ja tööohutuse nõuded ning töökeskkonna keemiliste ohutegurite piirnormid [RT I, 21.12.2022, 14]
LTU	Lietuva	Jsakymas dėl lietuvos higienos normos hn 23:2011 "cheminių medžiagų profesinio poveikio ribiniai dydžiai. Matavimo ir poveikio vertinimo bendrieji reikalavimai" patvirtinimo
LVA	Latvija	Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības saskarē ar kīmiskajām vielām darba vietās" (prot. Nr. 32 18. §; prot. Nr. 1 22. §)
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
SVK	Slovensko	NARIAĎENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023

Predicted no-effect concen	tration - PNEC							
Normal value in fresh wate	r			2	mç	g/l		
Normal value in marine wa	ter			0,2	mç	g/l		
Normal value for fresh water	er sediment			6,6	m	g/kg		
Normal value for marine wa	ater sediment			0,66	mç	g/kg		
Normal value for water, inte	ermittent release			18	m	g/l		
Normal value of STP micro	organisms			500	m	g/l		
Normal value for the food of	hain (secondary poison	ing)		333	m	g/kg		
Normal value for the terres	trial compartment			0,46	m	g/kg		
Health - Derived no-ef	fect level - DNEL / D Effects on consumers	DMEL			Effects on workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				12,5 mg/kg		•		•

bw/d



# **VALEO BRAKE AND CLUTCH FLUID DOT 3**

Revision nr. 4

Dated 04/08/2025

Printed on 04/08/2025

Page n. 6/18

Replaced revision:3 (Printed on: 14/11/2022)

117 mg/m3 Inhalation 195 mg/m3 125 mg/kg Skin 208 mg/kg bw/d bw/d **DIETHYLENE GLYCOL Threshold Limit Value** Country TWA/8h STEL/15min Remarks / Туре Observations mg/m3 mg/m3 ppm ppm AGW DEU 44 10 176 40 MAK DEU 44 10 176 40 DNK TI V 11 2,5 10 TLV EST 45 90 20 SKIN RD LTU 45 10 90 20 SKIN 10 RV LVA NGV/KGV SWE SKIN 45 10 90 20 NPEL S\/K 44 10 176 23 WEL GBR 101 Predicted no-effect concentration - PNEC Normal value in fresh water 10 ma/l Normal value in marine water 1 mg/l 20.9 Normal value for fresh water sediment mg/kg Normal value for marine water sediment 2.09 mg/kg Normal value for water, intermittent release 10 mg/l Normal value of STP microorganisms 199,5 mg/l Normal value for the terrestrial compartment 1,53 mg/kg Health - Derived no-effect level - DNEL / DMEL Effects on Effects on consumers workers Route of exposure Acute local Acute systemic Chronic local Chronic Acute local Acute Chronic local Chronic systemic systemic systemic Inhalation 60 mg/m3 12 ma/m3 12 mg/m3 44 mg/m3 VND 21 mg/kg/d VND Skin 43 mg/kg/d TRIETHYLENE GLYCOL **Threshold Limit Value** TWA/8h Remarks / Country STFL/15min Type Observations mg/m3 ma/m3 ppm ppm OEL EU 1000 Predicted no-effect concentration - PNEC Normal value in fresh water 10 mg/l Normal value in marine water 1 mg/l Normal value for fresh water sediment 46 mg/kg Normal value of STP microorganisms 10 mg/l Normal value for the terrestrial compartment 3.32 mg/kg Health - Derived no-effect level - DNEL / DMEL Effects on Effects on consumers workers Route of exposure Acute local Acute systemic Chronic local Chronic Acute local Acute Chronic local Chronic systemic systemic systemic



# **VALEO BRAKE AND CLUTCH FLUID DOT 3**

Revision nr. 4
Dated 04/08/2025

Printed on 04/08/2025

Page n. 7/18

Replaced revision:3 (Printed on: 14/11/2022)

nhalation			25 mg/m3	VND			50 mg/m3	VND
Skin			VND	20 mg/kg/d			VND	40 mg/kg/d
2,2'-metilimminodietano								
Predicted no-effect concentra	tion - PNEC							
Normal value in fresh water				0,1	mg.	/I		
Normal value in marine water				0,0125	mg	/I		
Normal value for fresh water s	sediment			0,89	mg	/kg		
Normal value for marine water	r sediment			0,111	mg.	/kg		
Normal value for water, interm	nittent release			1	mg	/I		
Normal value of STP microorg	ganisms			10	mg.	/I		
Normal value for the terrestria	l compartment			0,119	mg	/kg		
Health - Derived no-effec	Effects on				Effects on			
Route of exposure	consumers Acute local		Chronic local	Chronic	workers Acute local	Acute	Chronic local	Chronic
Inhalation				systemic		systemic		systemic 26 mg/m3
Skin								19 mg/kg
								- 5 5
2,6-di-tert-butyl-p-cresol								
Threshold Limit Value								
Type Cor	untry T	WA/8h		STEL/15min		Remarks Observat		
	m	ıg/m3	ppm	mg/m3	ppm			
TLV-ACGIH		2						
Predicted no-effect concentra	tion - PNEC							
Normal value in fresh water				0,199	μg/	1		
Normal value in marine water				0,02	μg/	1		
Normal value for fresh water s	sediment			99,6	μG	/kg		
Normal value for marine water	r sediment			9,96	μG,			
Normal value for water, interm	nittent release			1,99	μg/			
Normal value of STP microorg				0,17	mg.			
Normal value for the food cha		isonina)		8,33	mg			
		looriiiig/		47,69	μG			
Normal value for the terrestria	·	/ DME!		47,09	μG,	/NY		
Health - Derived no-effect	Effects on	. / DIVIEL			Effects on			
Route of exposure	consumers Acute local		Chronic local	Chronic	workers Acute local	Acute	Chronic local	Chronic
<u> </u>	Acute local		Smorile local	systemic	Acute Iocal	systemic	Omornic local	systemic
Oral		1 mg/kg bw/d		0,25 mg/kg bw/d				
Inhalation		3,1 mg/m3		0,78 mg/m3		18 mg/m3		4,4 mg/m3
Skin		6,7 mg/kg bw/d		1,7 mg/kg		19 mg/kg		4,7 mg/kg
				bw/d		bw/d		bw/d
METHYL-1H-BENZOTRIA	AZOLE							
Predicted no-effect concentra	tion - PNEC							
				0,008	mg.	/I		
Normal value in fresh water				0,008	mg.	/I		
Normal value in fresh water  Normal value in marine water								



# **VALEO BRAKE AND CLUTCH FLUID DOT 3**

Revision nr. 4

Dated 04/08/2025

Printed on 04/08/2025

Page n. 8/18

Replaced revision:3 (Printed on: 14/11/2022)

Normal value for marine water sediment	0.0025	mg/kg
	•	0 0
Normal value for water, intermittent release	0.086	mg/l
	-,	3
Normal value of STP microorganisms	39,4	mg/l
Tromai raido or C.T. Imeros gamento	33, 1	9
Normal value for the terrestrial compartment	0.0024	mg/kg
i Nomai value foi ine terrestrai compartmetti	0,0027	mg/kg

Health - Derived no-ef	fect level - DNEL / D	MEL						
	Effects on				Effects on			
	consumers				workers			
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral			VND	0,25 mg/kg				
Inhalation			VND	4,4 mg/m3			VND	8,8 mg/m3
Skin			VND	0,25 mg/kg			VND	0,5 mg/kg

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

#### 8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

#### HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

#### SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

#### EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

#### RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.



# **VALEO BRAKE AND CLUTCH FLUID DOT 3**

Revision nr. 4

Dated 04/08/2025

Printed on 04/08/2025

Page n. 9/18

Replaced revision:3 (Printed on: 14/11/2022)

#### ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

# **SECTION 9. Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	liquid	

Colour colourless to amber
Odour characteristic
Melting point / freezing point not available

Initial boiling point 253 °C Method:ISO 4925

Flammability not available

Lower explosive limit not applicable

Upper explosive limit not applicable

Flash point > 125 °C Method:ASTM D93

Auto-ignition temperature not available

Decomposition temperature not available

pH 9,3 Method:ISO 4925

Kinematic viscosity not available
Solubility soluble
Partition coefficient: n-octanol/water not available
Vapour pressure not available

Density and/or relative density 1,041 g/cm3 Method:ASTM 1122 Relative vapour density not available

Particle characteristics not applicable

#### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

VOC (Directive 2010/75/EU) 0
VOC (volatile carbon) 0

# **SECTION 10. Stability and reactivity**

#### 10.1. Reactivity

The product may react exothermically on contact with strong oxidising or reducing agents, strong acids or bases.

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol



# **VALEO BRAKE AND CLUTCH FLUID DOT 3**

Revision nr. 4

Dated 04/08/2025

Printed on 04/08/2025

Page n. 10/18

Replaced revision:3 (Printed on: 14/11/2022)

Hygroscopic.

DIETHYLENE GLYCOL

Hygroscopic.

#### 10.2. Chemical stability

Excessively high temperatures can cause thermal decomposition.

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Avoid exposure to: air.

Hygroscopic.

#### 10.3. Possibility of hazardous reactions

See paragraph 10.1.

DIETHYLENE GLYCOL

May form explosive mixtures with: perchlorates.

### 10.4. Conditions to avoid

Avoid overheating.

DIETHYLENE GLYCOL

Avoid exposure to: high temperatures.

#### 10.5. Incompatible materials

Oxidising or reducing agents. Strong acids or bases.

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Avoid contact with: strong acids, strong bases, water.

DIETHYLENE GLYCOL

Incompatible with: acids,bases,strong oxidising agents,strong reducing agents.

Keep away from: zinc.

2,6-di-tert-butyl-p-cresol

Avoid contact with: oxidising agents.

### 10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.



# **VALEO BRAKE AND CLUTCH FLUID DOT 3**

Revision nr. 4

Dated 04/08/2025

Printed on 04/08/2025

Page n. 11/18

Replaced revision:3 (Printed on: 14/11/2022)

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

Develops: carbon monoxide, carbon dioxide.

DIETHYLENE GLYCOL

In decomposition develops: carbon dioxide, carbon monoxide.

2,6-di-tert-butyl-p-cresol

In decomposition develops: carbon oxides.

# **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture: Not classified (no significant component)

ATE (Oral) of the mixture: 1538,46 mg/kg

ATE (Dermal) of the mixture: Not classified (no significant component)

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

LD50 (Dermal): 3540 mg/kg bw LD50 (Oral): 5170 mg/kg bw

DIETHYLENE GLYCOL

LD50 (Dermal): 13300 mg/kg LD50 (Oral): 16500 mg/kg

ATE (Oral): 500 mg/kg estimate from table 3.1.2 of Annex I of the CLP

(figure used for calculation of the acute toxicity estimate of the mixture)

LC50 (Inhalation mists/powders): > 4,6 mg/l/4h



# **VALEO BRAKE AND CLUTCH FLUID DOT 3**

Revision nr. 4

Dated 04/08/2025

Printed on 04/08/2025

Page n. 12/18

Replaced revision:3 (Printed on: 14/11/2022)

TRIETHYLENE GLYCOL

LD50 (Dermal): LD50 (Oral):

LC50 (Inhalation vapours):

16 ml/kg bw

> 2000 mg/kg bw

> 5.2 mg/l

2,6-di-tert-butyl-p-cresol

LD50 (Dermal):

> 2000 mg/kg dw

LD50 (Oral):

> 2930 mg/kg dw

### SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

# SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

#### RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

#### GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

#### CARCINOGENICITY

Does not meet the classification criteria for this hazard class

#### REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

#### STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

#### 11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

### **SECTION 12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.



# **VALEO BRAKE AND CLUTCH FLUID DOT 3**

evision nr. 4

Dated 04/08/2025

Printed on 04/08/2025

Page n. 13/18

Replaced revision:3 (Printed on: 14/11/2022)

### 12.1. Toxicity

2,6-di-tert-butyl-p-cresol

EC50 - for Crustacea > 0,61 mg/l/48h Chronic NOEC for Crustacea 0,316 mg/l

TRIETHYLENE GLYCOL

LC50 - for Fish 69800 mg/l/96h EC50 - for Crustacea > 10000 mg/l/48h

Reaction mass of 2-(2-(2-

butoxyethoxy)ethoxy)ethanol and 3,6,9,12-

tetraoxahexadecan-1-ol

 $LC50 - for Fish > 1800 \ mg/l/96h \\ EC50 - for Crustacea > 3200 \ mg/l/48h \\ EC50 - for Algae / Aquatic Plants 391 \ mg/l/72h \\ EC10 \ for Algae / Aquatic Plants 188 \ mg/l/72h$ 

DIETHYLENE GLYCOL

LC50 - for Fish 75200 mg/l
Chronic NOEC for Algae / Aquatic Plants 100 mg/l/72h

#### 12.2. Persistence and degradability

2,6-di-tert-butyl-p-cresol NOT rapidly degradable

TRIETHYLENE GLYCOL

Rapidly degradable DIETHYLENE GLYCOL

Rapidly degradable

# 12.3. Bioaccumulative potential

TRIETHYLENE GLYCOL

Partition coefficient: n-octanol/water -1,75

Reaction mass of 2-(2-(2-

butoxyethoxy)ethoxy)ethanol and 3,6,9,12-

tetraoxahexadecan-1-ol

Partition coefficient: n-octanol/water 0,51

DIETHYLENE GLYCOL

BCF 100

# 12.4. Mobility in soil

Information not available

# 12.5. Results of PBT and vPvB assessment



# **VALEO BRAKE AND CLUTCH FLUID DOT 3**

Revision nr. 4

Dated 04/08/2025

Printed on 04/08/2025

Page n. 14/18

Replaced revision:3 (Printed on: 14/11/2022)

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

#### 12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

#### 12.7. Other adverse effects

Information not available

# **SECTION 13. Disposal considerations**

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

# **SECTION 14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

#### 14.1. UN number or ID number

not applicable

### 14.2. UN proper shipping name

not applicable

#### 14.3. Transport hazard class(es)

not applicable

#### 14.4. Packing group



Revision nr. 4

Dated 04/08/2025

Printed on 04/08/2025

Service	VALLO BRAKE AND CLOTCH FLOID DOT 3	Page n. 15/18 Replaced revision:3 (Printed on: 14/11/2022)				
ot applicable						
4.5. Environmental hazards						
ot applicable						
4.6. Special precautions for user						
ot applicable						
4.7. Maritime transport in bulk acco	rding to IMO instruments					
nformation not relevant						
SECTION 15. Regulatory i	nformation					
15.1. Safety, health and environmer	ntal regulations/legislation specific for the substance or mixture					
eveso Category - Directive 2012/18/EU	U: None					
estrictions relating to the product or co	ontained substances pursuant to Annex XVII to EC Regulation 1907/2006					
roduct Point	3					
Contained substance	76					
Point	75					
	rketing and use of explosives precursors					
ot applicable						
substances in Candidate List (Art. 59 REACH)						
On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.						
substances subject to authorisation (Annex XIV REACH)						
lone						
	ting pursuant to Regulation (EU) 649/2012:					
lone						



# **VALEO BRAKE AND CLUTCH FLUID DOT 3**

Revision nr. 4

Dated 04/08/2025

Printed on 04/08/2025

Page n. 16/18

Replaced revision:3 (Printed on: 14/11/2022)

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

#### 15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

Reaction mass of 2-(2-(2-butoxyethoxy)ethoxy)ethanol and 3,6,9,12-tetraoxahexadecan-1-ol

DIETHYLENE GLYCOL

TRIETHYLENE GLYCOL

2,6-di-tert-butyl-p-cresol

# **SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4 Acute toxicity, category 4

Eye Dam. 1 Serious eye damage, category 1

Eye Irrit. 2 Eye irritation, category 2

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

H302 Harmful if swallowed.

H318 Causes serious eye damage.H319 Causes serious eye irritation.

H410 Very toxic to aquatic life with long lasting effects.

#### LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization

Revision nr. 4

Dated 04/08/2025

Printed on 04/08/2025

Page n. 17/18

Replaced revision:3 (Printed on: 14/11/2022)

### **VALEO BRAKE AND CLUTCH FLUID DOT 3**

- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

#### GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EÚ) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP) 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP) 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP) 25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- 26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

#### Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.



# **VALEO BRAKE AND CLUTCH FLUID DOT 3**

Revision nr. 4

Dated 04/08/2025

Printed on 04/08/2025

Page n. 18/18

Replaced revision:3 (Printed on: 14/11/2022)

CALCULATION METHODS FOR CLASSIFICATION
Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.
Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.
Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

msds for B2C.

Changes to previous review: The following sections were modified: 01 / 03.