

VALEO PROTECTIV 50 - G12 TYPE

Revision nr. 4

Dated 07/05/2025

Printed on 07/05/2025

Page n. 1/15

Replaced revision:3 (Printed on: 14/11/2022)

Safety Data Sheet According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

VALEO PROTECTIV 50 - G12 TYPE Product name

UFI: E1E0-80KU-E008-ME54

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use PREDILUTED COOLANT (for B2C)

Identified Uses	Industrial	Professional	Consumer	
De-icing and anti-icing applications		4		
	❤	✓	❤	
1.3. Details of the supplier of the safety data sl	heet			
Name	Valeo Service Africa	& Overseas		
Full address	70, rue Pleyel			
District and Country	93285 Saint-Denis Co	edex		
	France			
	Tel. +33 (0)1 49 45 32	32		
	10 100 (0)1 40 40 02	. 02		
e-mail address of the competent person				
responsible for the Safety Data Sheet	alert.export@valeo.c	om		
1.4. Emergency telephone number				
For urgent inquiries refer to	MA: 212 80-1000180			
	TN: 71 335 500			
	DZ : 3016			
	IL: 04-7771900			
	ZA: 27861555777			
	AU: 131126			
	NZ: 0800 764 766			
	NC: 01 40 05 48 48			
	FR: 01 40 05 48 48			

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Acute toxicity, category 4 H302 Harmful if swallowed.

CI: 185 SN: 15

Specific target organ toxicity - repeated exposure, category 2 H373 May cause damage to organs through prolonged or repeated

exposure.



VALEO PROTECTIV 50 - G12 TYPE

Revision nr. 4

Dated 07/05/2025

Printed on 07/05/2025

Page n. 2/15

Replaced revision:3 (Printed on: 14/11/2022)

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:





Signal words: Warning

Hazard statements:

H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P262 Do not get in eyes, on skin, or on clothing.

P264 Wash hands thoroughly after handling.

P301+P312 IF SWALLOWED: Call a POISON CENTER / doctor / . . . / if you feel unwell.

P314 Get medical advice / attention if you feel unwell.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

P270 Do not eat, drink or smoke when using this product.

Contains: ETHANEDIOL

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration \geq 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures



VALEO PROTECTIV 50 - G12 TYPE

LD50 Oral: >300 mg/kg

Revision nr. 4

Dated 07/05/2025

Printed on 07/05/2025

Page n. 3/15

Replaced revision:3 (Printed on: 14/11/2022)

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)

ETHANEDIOL

INDEX 603-027-00-1 45 ≤ x < 50 Acute Tox. 4 H302, STOT RE 2 H373

EC 203-473-3 CAS 107-21-1

REACH Reg. 01-2119456816-28-

XXXX

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If symptoms occur, whether acute or delayed, consult a doctor.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITÄBLE EXTINGUISHING EQUIPMENT



VALEO PROTECTIV 50 - G12 TYPE

Revision nr. 4

Dated 07/05/2025

Printed on 07/05/2025

Page n. 4/15

Replaced revision:3 (Printed on: 14/11/2022)

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)



VALEO PROTECTIV 50 - G12 TYPE

Revision nr. 4

Dated 07/05/2025

Printed on 07/05/2025

Page n. 5/15

Replaced revision:3 (Printed on: 14/11/2022)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory references:

BGR	България	НАРЕДБА № 13 ОТ 30 ДЕКЕМВРИ 2003 Г. ЗА ЗАЩИТА НА РАБОТЕЩИТЕ ОТ РИСКОВЕ, СВЪРЗАНИ С ЕКСПОЗИЦИЯ НА ХИМИЧНИ АГЕНТИ ПРИ РАБОТА (изм. ДВ. бр.5 от 17 Януари 2020г.)
CZE	Česká Republika	NAŘÍZENÍ VLÁDY ze dne 10. května 2021, kterým se mění nařízení vlády č. 361/2007 Sb., kterým se stanoví podmínky ochrany zdraví při práci
DEU	Deutschland	Forschungsgemeinschaft MAK- und BAT-Werte-Liste 2022 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe Mitteilung 58
DNK	Danmark	Bekendtgørelse om grænseværdier for stoffer og materialer - BEK nr 1458 af 13/12/2019
ESP	España	Límites de exposición profesional para agentes químicos en España 2023
EST	Eesti	Ohtlike kemikaalide ja neid sisaldavate materjalide kasutamise töötervishoju ja tööohutuse nõuded ning
	200	töökeskkonna keemiliste ohutegurite piirnormid [RT I, 21.12.2022, 14]
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28
1107	Tance	décembre 2021
FIN	Suomi	HTP-VÄRDEN 2020. Koncentrationer som befunnits skadliga. SOCIAL - OCH
1 111	Suomi	HÄLSOVÅRDSMINISTERIETS PUBLIKATIONER 2020:25
GRC	Ελλάδα	Π.Δ. 26/2020 (ΦΕΚ 50/Α` 6.3.2020) Εναρμόνιση της ελληνικής νομοθεσίας προς τις διατάξεις των οδηγιών
GRC	Ελλάδα	
		2017/2398/ΕΕ, 2019/130/ΕΕ και 2019/983/ΕΕ «για την τροποποίηση της οδηγίας 2004/37/ΕΚ ``σχετικά με
		την προστασία των εργαζομένων από τους κινδύνους που συνδέονται με την έκθεση σε καρκινογόνους ή
		μεταλλαξιγόνους παράγοντες κατά την εργασία``»
HUN	Magyarország	Az innovációért és technológiáért felelős miniszter 5/2020. (II. 6.) ITM rendelete a kémiai kóroki tényezők
		hatásának kitett munkavállalók egészségének és biztonságának védelméről
HRV	Hrvatska	Pravilnik o izmjenama i dopunama Pravilnika o zaštiti radnika od izloženosti opasnimkemikalijama na radu,
		graničnim vrijednostima izloženosti i biološkim graničnim vrijednostima (NN 1/2021)
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
LTU	Lietuva	Jsakymas dėl lietuvos higienos normos hn 23:2011 "cheminių medžiagų profesinio poveikio ribiniai dydžiai.
		Matavimo ir poveikio vertinimo bendrieji reikalavimai"
		patvirtinimo
LVA	Latvija	Grozījumi Ministru kabineta 2007. gada 15. maija noteikumos Nr. 325 "Darba aizsardzības prasības
		saskarē ar ķīmiskajām vielām darba vietās" (prot. Nr. 32 18. §; prot. Nr. 1 22. §)
NOR	Norge	Forskrift om endring i forskrift om tiltaksverdier og grenseverdier for fysiske og kjemiske faktorer i
		arbeidsmiljøet samt smitterisikogrupper for biologiske faktorer (forskrift om tiltaks- og grenseverdier), 21.
		august 2018 nr. 1255
NLD	Nederland	Arbeidsomstandighedenregeling. Lijst van wettelijke grenswaarden op grond van de artikelen 4.3, eerste
		lid, en 4.16, eerste lid, van het Arbeidsomstandighedenbesluit
SWE	Sverige	Hygieniska gränsvärden, Arbetsmiljöverkets föreskrifter och allmänna råd om hygieniska gränsvärden (AFS 2018:1)
SVK	Slovensko	NARIADENIE VLÁDY Slovenskej republiky z 12. augusta 2020, ktorým sa mení a dopĺňa nariadenie vlády
		Slovenskej republiky č. 356/2006 Z. z. o ochrane zdravia zamestnancov pred rizikami súvisiacimi s
		expozíciou karcinogénnym a mutagénnym faktorom pri práci v znení neskorších predpisov
TUR	Türkiye	Kimyasal Maddelerle Calışmalarda Sağlık ve Güvenlik Önlemleri Hakkında Yönetmelik 12.08.2013 / 28733;
		20.10.2023 / 32345.
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983;
		Directive (EU) 2017/2398: Directive (EU) 2017/164: Directive 2009/161/EU: Directive 2006/15/EC: Directive
		2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2023
	1277.00111	7.0011 2020

ETHANEDIOL

Threshold Li	mit Value						
Туре	Country	TWA/8h		STEL/15min		Remarks / Observations	
		mg/m3	ppm	mg/m3	ppm		
TLV	BGR	52		104		SKIN	
TLV	CZE	50		100		SKIN	
AGW	DEU	26	10	52	20	SKIN	
MAK	DEU	26	10	52	20	SKIN	
TLV	DNK	26	10			SKIN	
VLA	ESP	52	20	104	40	SKIN	



VALEO PROTECTIV 50 - G12 TYPE

Revision nr. 4

Dated 07/05/2025

Printed on 07/05/2025

Page n. 6/15

Replaced revision:3 (Printed on: 14/11/2022)

HTP	FIN	50			100	40	SKIN		
TLV	GRC	125		50	125	50			
AK	HUN	52			104				
GVI/KGVI	HRV	52		20	104	40	SKIN		
VLEP	ITA	52		20	104	40	SKIN		
RD	LTU	25		10	50	20	SKIN		
RV	LVA	52		20	104	40	SKIN		
TLV	NOR			25			SKIN		
TGG	NLD	52			104		SKIN		
NGV/KGV	SWE	25		10	50	20	SKIN		
NPEL	SVK	52		20	104		SKIN		
ESD	TUR	52		20	104	40	SKIN		
WEL	GBR	52		20	104	40			
OEL	EU	52		20	104	40	SKIN		
TLV-ACGIH					100 (C)				
Predicted no-effect	concentration - PNE	:C							
Normal value in fres	sh water				10	mg,	1		
Normal value in mar	rine water				1	mg,	1		
Normal value for free	sh water sediment				20,9	mg,	/kg		
Normal value for wa	ter, intermittent rele	ase			10	mg,	1		
Normal value of STF	P microorganisms				199,5	mg,	1		
		ment			1,53	mg	/kg		
Normal value for the	e terrestrial compart								
Normal value for the Health - Derived	no-effect level -	DNEL / Dects on	MEL			Effects on workers			
Health - Derived	no-effect level - Effe	DNEL / D	Acute systemic	Chronic local	Chronic	Effects on workers Acute local	Acute	Chronic local	Chronic
Health - Derived Route of exposure	no-effect level - Effe	DNEL / Dects on sumers		Chronic local 7 mg/m3	Chronic systemic VND	workers	Acute systemic	Chronic local 35 mg/m3	Chronic systemic VND
	no-effect level - Effe	DNEL / Dects on sumers			systemic	workers			systemic VND
Route of exposure Inhalation Skin	no-effect level - Effe con Acu	DNEL / Dects on sumers		7 mg/m3	systemic VND	workers		35 mg/m3	systemic VND
Health - Derived Route of exposure Inhalation	no-effect level - Effect con Acu	DNEL / D ects on sumers te local		7 mg/m3	systemic VND	workers		35 mg/m3	systemic
Route of exposure Inhalation Skin DISODIUM SUCC	no-effect level - Effecton Acus Acus CINATE concentration - PNE	DNEL / D ects on sumers te local		7 mg/m3	systemic VND	workers	systemic	35 mg/m3	systemic VND
Route of exposure Inhalation Skin DISODIUM SUCC	no-effect level - Effect con Acu Acu CINATE concentration - PNE	DNEL / D ects on sumers te local		7 mg/m3	systemic VND 53 mg/kg/d	workers Acute local	systemic	35 mg/m3	systemic VND
Route of exposure Inhalation Skin DISODIUM SUCC Predicted no-effect of Normal value in fres	CINATE concentration - PNE sh water	DNEL / D ects on sumers te local		7 mg/m3	systemic VND 53 mg/kg/d 100	workers Acute local µg/ µg/	systemic	35 mg/m3	systemic VND
Route of exposure Inhalation Skin DISODIUM SUCC Predicted no-effect of Normal value in frest Normal value in man	CINATE concentration - PNE sh water rine water sh water sediment	DNEL / D ects on sumers te local		7 mg/m3	systemic VND 53 mg/kg/d 100 10	workers Acute local	systemic	35 mg/m3	systemic VND
Route of exposure Inhalation Skin DISODIUM SUCC Predicted no-effect of Normal value in fres Normal value for free Normal value for ma	CINATE concentration - PNE sh water rine water sh water sediment	DNEL / D ects on sumers tte local	Acute systemic	7 mg/m3	systemic VND 53 mg/kg/d 100 10 480	workers Acute local	systemic L kg/d kg/d	35 mg/m3	systemic VND
Route of exposure Inhalation Skin DISODIUM SUCC Predicted no-effect of Normal value in man Normal value for free Normal value for man	CINATE concentration - PNE sh water rine water sediment arine water, intermitt	DNEL / D ects on sumers te local EC	Acute systemic	7 mg/m3	systemic VND 53 mg/kg/d 100 10 480 48	workers Acute local	L L kg/d kg/d	35 mg/m3	systemic VND
Route of exposure Inhalation Skin DISODIUM SUCC Predicted no-effect of Normal value in fres Normal value for free Normal value for ma Normal value for ma Normal value for ma Normal value for free	CINATE concentration - PNE sh water rine water sh water sediment arine water, intermitter	DNEL / D ects on sumers te local te control te tent release	Acute systemic	7 mg/m3	systemic VND 53 mg/kg/d 100 10 480 48	workers Acute local μg/ μg/ μg/ μg/ μg/ mg. mg.	L L kg/d kg/d	35 mg/m3	systemic VND
Route of exposure Inhalation Skin DISODIUM SUCC Predicted no-effect of Normal value in fres Normal value for free	CINATE concentration - PNE sh water rine water sh water sediment arine water, intermitter arine water, intermitter et eterrestrial compart no-effect level -	DNEL / D ects on sumers ite local EC t teent release ment DNEL / D	Acute systemic	7 mg/m3	systemic VND 53 mg/kg/d 100 10 480 48 1	workers Acute local	systemic L kg/d kg/d	35 mg/m3	systemic VND
Route of exposure Inhalation Skin DISODIUM SUCC Predicted no-effect of Normal value in frest Normal value for free Normal value for man Normal value for man Normal value for man Normal value for free Normal value for free Normal value for free Normal value for the Normal value for	CINATE Concentration - PNE sh water rine water sh water sediment arine water, intermitter arine water, intermitter are terrestrial compart no-effect level -	DNEL / D ects on sumers te local t tent release ment	Acute systemic	7 mg/m3	systemic VND 53 mg/kg/d 100 10 480 48 1	workers Acute local μg/ μg/ μg/ μg/ μg/ mg. mg.	systemic L kg/d kg/d	35 mg/m3	systemic VND
Route of exposure Inhalation Skin DISODIUM SUCC Predicted no-effect of Normal value in frest Normal value for free Normal value for man Normal value for man Normal value for man Normal value for free Normal value for free Normal value for free Normal value for the Normal value for	CINATE Concentration - PNE sh water rine water sh water sediment arine water, intermitter arine water, intermitter the terrestrial compart no-effect level - Effection	t tent release ment DNEL / D	Acute systemic	7 mg/m3	systemic VND 53 mg/kg/d 100 10 480 48 1	workers Acute local	systemic L kg/d kg/d	35 mg/m3	systemic VND



Normal value for the terrestrial compartment

VALEO SERVICE

VALEO PROTECTIV 50 - G12 TYPE

Revision nr. 4

Dated 07/05/2025

Printed on 07/05/2025

Page n. 7/15

Replaced revision:3 (Printed on: 14/11/2022)

Inhalation	7,25 mg/m3	41,1 mg/m3
Skin	4,17 mg/kg bw/d	11,7 mg/kg bw/d

TETRASODIUM ETHYLENE DIAMINE TETRAACETATE Predicted no-effect concentration - PNEC Normal value in fresh water 2,2 mg/l Normal value in marine water 0,22 mg/l Normal value of STP microorganisms 43 mg/l

0.72

mg/l

Health - Derived no-effect level - DNEL / DMEL									
	Effects on				Effects on				
	consumers				workers				
Route of exposure	Acute local	Acute systemic	Chronic local	Chronic	Acute local	Acute	Chronic local	Chronic	
				systemic		systemic		systemic	
Oral			VND	25 mg/kg/d					
Inhalation	1.5 mg/m3	1.5 ma/m3	1.5 mg/m3	1.5 ma/m3	2.5 ma/m3	2.5 ma/m3	2.5 ma/m3	2.5 mg/m3	

Legend:

(C) = CEILING; INHAL = Inhalable Fraction; RESP = Respirable Fraction; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Exposure levels must be kept as low as possible to avoid significant build-up in the organism. Manage personal protective equipment so as to guarantee maximum protection (e.g. reduction in replacement times).

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

In the presence of risks of exposure to splashes or squirts during work, adequate mouth, nose and eye protection should be used to prevent accidental absorption.

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold



VALEO PROTECTIV 50 - G12 TYPE

Revision nr. 4

Dated 07/05/2025

Printed on 07/05/2025

Page n. 8/15

Replaced revision:3 (Printed on: 14/11/2022)

values considered. Use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Information

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties Appearance	Value liquid
Colour	yellow or pink
Odour	characteristic
Melting point / freezing point	-35 °C
Initial boiling point	> 108 °C
Flammability	not available
Lower explosive limit	4,9 % (v/v)
Upper explosive limit	14,6 % (v/v)
Flash point	> 125 °C
Auto-ignition temperature	> 400 °C
Decomposition temperature	not available
рН	7,5 - 10
Kinematic viscosity	not available
Solubility	soluble
Partition coefficient: n-octanol/water	-1,93
Vapour pressure	not available
Density and/or relative density	1,050 - 1,080
Relative vapour density	not available
Particle characteristics	not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available

SECTION 10. Stability and reactivity



VALEO PROTECTIV 50 - G12 TYPE

Revision nr. 4

Dated 07/05/2025

Printed on 07/05/2025

Page n. 9/15

Replaced revision:3 (Printed on: 14/11/2022)

10.1. Reactivity

The product may react exothermically on contact with strong oxidising or reducing agents, strong acids or bases.

10.2. Chemical stability

Excessively high temperatures can cause thermal decomposition.

ETHANEDIOL

Reacts with strong oxidising agents.

10.3. Possibility of hazardous reactions

See paragraph 10.1.

10.4. Conditions to avoid

Avoid overheating.

ETHANEDIOL

ETHANEDIOL: avoid exposure to sources of heat and naked flames.

10.5. Incompatible materials

Oxidising or reducing agents. Strong acids or bases.

Do not store in zinc-coated.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

ETHANEDIOL

ETHANEDIOL: hydroxyacetaldehyde, glyoxal, acetaldehyde, methane, formaldehyde, carbon monoxide, hydrogen.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

ETHANEDIOL



VALEO PROTECTIV 50 - G12 TYPE

Revision nr. 4

Dated 07/05/2025

Printed on 07/05/2025

Page n. 10/15

Replaced revision:3 (Printed on: 14/11/2022)

ETHANEDIOL: following ingestion it initially stimulates the CNS; later on depression results. Renal damage with anuria and uremia may occur. Symptoms of over exposure are: vomiting, somnolence, difficulty in breathing, convulsions. The lethal dose in man is approximately 1.4 l/kg. The way of entry is inhalation and ingestion.

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture: Not classified (no significant component)

ATE (Oral) of the mixture: 657,24 mg/kg

ATE (Dermal) of the mixture: Not classified (no significant component)

ETHANEDIOL

LD50 (Dermal): > 5000 mg/kg Rabbit

LD50 (Oral): > 300 mg/kg

DISODIUM SUCCINATE

LD50 (Dermal): 2000 mg/kg LD50 (Oral): 2000 mg/kg

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class



VALEO PROTECTIV 50 - G12 TYPE

Revision nr. 4

Dated 07/05/2025

Printed on 07/05/2025

Page n. 11/15

Replaced revision:3 (Printed on: 14/11/2022)

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

DISODIUM SUCCINATE

EC50 - for Crustacea 100 mg/l/48h EC50 - for Algae / Aquatic Plants 100,99 mg/l/72h

ETHANEDIOL

12.2. Persistence and degradability

DISODIUM SUCCINATE

Rapidly degradable ETHANEDIOL

Rapidly degradable

12.3. Bioaccumulative potential

ETHANEDIOL

Partition coefficient: n-octanol/water -1,93

12.4. Mobility in soil

ETHANEDIOL

ETHANEDIOL: very mobile in soil.

12.5. Results of PBT and vPvB assessment

ETHANEDIOL



VALEO PROTECTIV 50 - G12 TYPE

Revision nr. 4

Dated 07/05/2025

Printed on 07/05/2025

Page n. 12/15

Replaced revision:3 (Printed on: 14/11/2022)

ETHANEDIOL: is not considered to be PBT or vPvB.

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group



Dated 07/05/2025

Printed on 07/05/2025

			Page n. 13/15
	Service		Replaced revision:3 (Printed on: 14/11/2022)
not applicable			
14.5. Environi	nental hazards		
not applicable			
ا 14.6. Special	precautions for user		
not applicable			
14.7. Maritime	transport in bulk acco	ording to IMO instruments	
nformation no	relevant		
SECTION	I 15. Regulatory	information	
15.1. Safety,	health and environme	ental regulations/legislation specific for the substance or mixture	
Seveso Catego	ory - Directive 2012/18/E	EU: None	
Restrictions re	ating to the product or c	contained substances pursuant to Annex XVII to EC Regulation 1907/2006	
Product			
Point		3	
Regulation (EL	J) 2019/1148 - on the ma	arketing and use of explosives precursors	
not applicable			
Substances in	Candidate List (Art. 59 I	REACH)	
On the basis o	available data, the prod	duct does not contain any SVHC in percentage ≥ than 0,1%.	
Substances su	bject to authorisation (A	nnex XIV REACH)	
None			
Substances su	bject to exportation repo	orting pursuant to Regulation (EU) 649/2012:	
None			
<u>Substanc</u> es su	bject to the Rotterdam (Convention:	
None			
-			



VALEO PROTECTIV 50 - G12 TYPE

Revision nr. 4

Dated 07/05/2025

Printed on 07/05/2025

Page n. 14/15

Replaced revision:3 (Printed on: 14/11/2022)

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment

A chemical safety assessment has been performed for the following contained substances

ETHANEDIOL

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4 Acute toxicity, category 4

STOT RE 2 Specific target organ toxicity - repeated exposure, category 2

H302 Harmful if swallowed.

H373 May cause damage to organs through prolonged or repeated exposure.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).



VALEO PROTECTIV 50 - G12 TYPE

Revision nr. 4

Dated 07/05/2025

Printed on 07/05/2025

Page n. 15/15

Replaced revision:3 (Printed on: 14/11/2022)

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
- 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EÚ) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP)
- 15. Regulation (EU) 2019/521 (XII Atp. CLP)
 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- 23. Delegated Regulation (UE) 2023/707
- 24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
- 25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
- 26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.