



**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

Page n. 1/21

Replaced revision:3 (Dated: 12/04/2019)

## Safety Data Sheet

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name **BRAKE FLUID DOT4 – 401702-402104-402106-402401-402402-402403-402404-402405**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use **BRAKE FLUID DOT4 (for B2C)**

Identified Uses	Industrial	Professional	Consumer
Functional Fluids	✓	✓	✓

#### 1.3. Details of the supplier of the safety data sheet

Name **Valeo Service Africa & Overseas**  
Full address **70 rue Pleyel**  
District and Country **93285 Saint Denis Cedex  
France**  
Tel. **+33 (0)1 49 45 32 32**

e-mail address of the competent person  
responsible for the Safety Data Sheet

[vsao.contact.mailbox@valeo.com](mailto:vsao.contact.mailbox@valeo.com)

#### 1.4. Emergency telephone number

For urgent inquiries refer to **+33 (0)1 49 45 32 32 (business hours)**

### SECTION 2. Hazards identification

#### 2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Reproductive toxicity, category 2

H361d

Suspected of damaging the unborn child.

#### 2.2. Label elements



VALEO SERVICE SAS  
MEAO

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

**BRAKE FLUID DOT4**  
**(401702-402104-402106-402401-402402-402403-402404-402405)**

Page n. 2/21

Replaced revision:3 (Dated: 12/04/2019)

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Warning

Hazard statements:

**H361d** Suspected of damaging the unborn child.

Precautionary statements:

**P501** Dispose of contents/container in accordance with local/regional/national/international regulations.  
**P102** Keep out of reach of children.  
**P280** Wear protective gloves/ protective clothing / eye protection / face protection.  
**P101** If medical advice is needed, have product container or label at hand.  
**P405** Store locked up.  
**P201** Obtain special instructions before use.

**Contains:** tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] borate

### 2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

## SECTION 3. Composition/information on ingredients

### 3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
tris[2-[2-(2-methoxyethoxy)ethoxy]ethyl] borate		
CAS 30989-05-0	10 ≤ x < 15	Repr. 2 H361d
EC 250-418-4		
INDEX -		
Reg. no. 01-2119462824-33-xxxx		
<b>Reaction mass of 2-[2-(2-butoxyethoxy)ethoxy]ethanol</b>		



**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

Page n. 3/21

Replaced revision:3 (Dated: 12/04/2019)

CAS -  $6 \leq x < 12$  Eye Dam. 1 H318

EC 907-996-4

INDEX -

Reg. no. 01-2119531322-53-xxxx

**ESTER OF BORIC ACID**

CAS 71035-05-7  $5 \leq x < 7$  Acute Tox. 4 H302

EC

INDEX -

Reg. no. 01-2120766655-42-xxxx

**TRIETHYLENE GLYCOL**

CAS 112-27-6  $2 \leq x < 4$  Substance with a community workplace exposure limit.

EC 203-953-2

INDEX -

Reg. no. 01-2119438366-35-xxxx

**2-(2-BUTOXYETHOXY)ETHANOL**

CAS 112-34-5  $1 \leq x < 3$  Eye Irrit. 2 H319

EC 203-961-6

INDEX 603-096-00-8

Reg. no. 01-2119475104-44-xxxx

**DIETHYLENE GLYCOL**

CAS 111-46-6  $1 \leq x < 2$  Acute Tox. 4 H302

EC 203-872-2

INDEX 603-140-00-6

Reg. no. 01-2119457857-21-xxxx

**DI-ISOPROPANOLAMINE**

CAS 110-97-4  $0 \leq x < 1$  Eye Irrit. 2 H319

EC 203-820-9

INDEX 603-083-00-7

Reg. no. 01-2119475444-34-xxxx

**DIETHYLENE GLYCOL  
MONOMETHYL ETHER**

CAS 111-77-3  $0 \leq x < 1$  Repr. 2 H361d

EC 203-906-6

INDEX 603-107-00-6

Reg. no. 01-2119475100-52-xxxx

**2,6-di-tert-butyl-p-cresol**

CAS 128-37-0  $0 \leq x < 0,2$  Aquatic Chronic 1 H410 M=1

EC 204-881-4

INDEX -

Reg. no. 01-2119480433-40-xxxx



**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

Page n. 4/21

Replaced revision:3 (Dated: 12/04/2019)

The full wording of hazard (H) phrases is given in section 16 of the sheet.

## SECTION 4. First aid measures

### 4.1. Description of first aid measures

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

**INGESTION:** Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

**INHALATION:** Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

### 4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

### 4.3. Indication of any immediate medical attention and special treatment needed

Information not available

## SECTION 5. Firefighting measures

### 5.1. Extinguishing media

#### SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

#### UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

### 5.2. Special hazards arising from the substance or mixture

#### HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

### 5.3. Advice for firefighters

#### GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

#### SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## SECTION 6. Accidental release measures



**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

Page n. 5/21

Replaced revision:3 (Dated: 12/04/2019)

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## SECTION 7. Handling and storage

### 7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

## SECTION 8. Exposure controls/personal protection

### 8.1. Control parameters

Regulatory References:

DEU	Deutschland	TRGS 900 (Fassung 31.1.2018 ber.) - Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
DNK	Danmark	Graenseværdier per stoffer og materialer
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2017
EST	Eesti	Töökeskkonna keemiliste ohutegurite piinormid 1. Vastu võetud 18.09.2001 nr 293 RT I 2001, 77, 460 - Redaktsiooni jõustumise kp: 01.01.2008
FIN	Suomi	HTP-arvot 2012. Haitallisiksi tunnetut pitoisuudet - Sosiaali- ja terveysministeriön julkaisu 2012:5



**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

Page n. 6/21

Replaced revision:3 (Dated: 12/04/2019)

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

GBR	United Kingdom	EH40/2005 Workplace exposure limits
GRC	Ελλάδα	ΕΦΗΜΕΡΙΣ ΤΗΣ ΚΥΒΕΡΝΗΣΕΩΣ - ΤΕΥΧΟΣ ΠΡΩΤΟ Αρ. Φύλλου 19 - 9 Φεβρουαρίου 2012
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
LTU	Lietuva	DEL LIETUVOS HIGIENOS NORMOS HN 23:2007 CHEMINIJ MEDZIAGU 2007 m. spalio 15 d. Nr. V-827/A1-287
LVA	Latvija	Kīmisko vielu aroda ekspozīcijas robežvērtības (AER) darba vietas gaisā 2012
NLD	Nederland	Databank of the social and Economic Council of Netherlands (SER) Values, AF 2011:18
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 12 czerwca 2018 r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República I 26; 2012-02-06
ROU	România	Monitorul Oficial al României 44; 2012-01-19
SVK	Slovensko	NARIADENIE VLADY Slovenskej republiky z 20. júna 2007
SVN	Slovenija	Uradni list Republike Slovenije 04.06.2015 (1602) - Pravilnik o spremembah in dopolnitvah Pravilnika o varovanju delavcev pred tveganji zaradi izpostavljenosti kemičnim snovem pri delu
SWE	Sverige	Occupational Exposure Limit Values, AF 2011:18
EU	OEL EU	Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2018

**Reaction mass of 2-[2-(2-Butoxyethoxy)ethoxy]ethanol**

Predicted no-effect concentration - PNEC

Normal value in fresh water	4,5	mg/l
Normal value in marine water	0,31	mg/l
Normal value for fresh water sediment	6,6	mg/kg
Normal value for marine water sediment	0,66	mg/kg
Normal value for water, intermittent release	24,9	mg/l
Normal value of STP microorganisms	500	mg/l
Normal value for the terrestrial compartment	1,32	mg/kg

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				2,5 mg/kg bw/d				
Inhalation				117 mg/m3				195 mg/m3
Skin				25 mg/kg bw/d				50 mg/kg bw/d

**TRIETHYLENE GLYCOL**

**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
OEL	EU	1000			

Predicted no-effect concentration - PNEC

Normal value in fresh water	10	mg/l
Normal value in marine water	1	mg/l
Normal value for fresh water sediment	46	mg/kg
Normal value of STP microorganisms	10	mg/l
Normal value for the terrestrial compartment	3,32	mg/kg



**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

Page n. 7/21

Replaced revision:3 (Dated: 12/04/2019)

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers			Effects on workers				
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation			25 mg/m3	VND			50 mg/m3	VND
Skin			VND	20 mg/kg/d			VND	40 mg/kg/d

**2-(2-BUTOXYETHOXY)ETHANOL**

**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU	67	10	100,5	15	
TLV	DNK	67,5	10			
VLA	ESP	67,5	10	101,2	15	
HTP	FIN	68	10			
TLV	GRC	67,5	10	101,2	15	
VLEP	ITA	67,5	10	101,2	15	
RD	LTU	100	15	200	30	
RV	LVA	67,5	10	101,2	15	
OEL	NLD	50		100		SKIN
NDS	POL	67		100		
VLE	PRT	67,5	10	101,2	15	
TLV	ROU	150		250		
NPHV	SVK	67,5	10	101,2		
MV	SVN	67,5	10	101,25	15	
MAK	SWE	100	15	200	30	
OEL	EU	67,5	10	101,2	15	
TLV-ACGIH		66	10			

**DIETHYLENE GLYCOL**

**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	44	10	176	40	
MAK	DEU	44	10	176	40	
TLV	DNK	11	2,5			
TLV	EST	45	10	90	20	SKIN
WEL	GBR	101	23			
RD	LTU	45	10	90	20	SKIN
RV	LVA	10				



**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

Page n. 8/21

Replaced revision:3 (Dated: 12/04/2019)

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

NPHV	SVK	44	10	176		
------	-----	----	----	-----	--	--

MAK	SWE	45	10	90	20	SKIN
-----	-----	----	----	----	----	------

**Predicted no-effect concentration - PNEC**

Normal value in fresh water		10		mg/l
-----------------------------	--	----	--	------

Normal value in marine water		1		mg/l
------------------------------	--	---	--	------

Normal value for marine water sediment		20,9		mg/kg
--	--	------	--	-------

Normal value of STP microorganisms		10		mg/l
------------------------------------	--	----	--	------

Normal value for the terrestrial compartment		1,53		mg/kg
--	--	------	--	-------

**Health - Derived no-effect level - DNEL / DMEL**

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation							12 mg/m3	VND
Skin							VND	53 mg/kg/d

**DIETHYLENE GLYCOL MONOMETHYL ETHER**

**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
VLA	ESP	50,1	10		SKIN
HTP	FIN	50,1	10		SKIN
TLV	GRC	50,1	10		
VLEP	ITA	50,1	10		SKIN
NDS	POL	50			
VLE	PRT	50,1	10		SKIN
TLV	ROU	50,1	10		SKIN
MV	SVN	50,1	10		SKIN
OEL	EU	50,1	10		SKIN

**2,6-di-tert-butyl-p-cresol**

**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
TLV-ACGIH		2			

**Predicted no-effect concentration - PNEC**

Normal value in fresh water		0,199		µg/l
-----------------------------	--	-------	--	------

Normal value in marine water		0,02		µg/l
------------------------------	--	------	--	------

Normal value for fresh water sediment		99,6		µG/kg
---------------------------------------	--	------	--	-------

Normal value for marine water sediment		9,96		µG/kg
--	--	------	--	-------

Normal value for water, intermittent release		1,99		µg/l
--	--	------	--	------





**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

Page n. 9/21

Replaced revision:3 (Dated: 12/04/2019)

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

Normal value of STP microorganisms	0,17	mg/l
Normal value for the food chain (secondary poisoning)	8,33	mg/kg
Normal value for the terrestrial compartment	47,69	µG/kg

Health - Derived no-effect level - DNEL / DMEL								
Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral		1 mg/kg bw/d		0,25 mg/kg bw/d				
Inhalation		3,1 mg/m3		0,78 mg/m3	18 mg/m3			4,4 mg/m3
Skin		6,7 mg/kg bw/d		1,7 mg/kg bw/d	19 mg/kg bw/d			4,7 mg/kg bw/d

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified.

**8.2. Exposure controls**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

**HAND PROTECTION**

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear airtight protective goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.



**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

Page n. 10/21

Replaced revision:3 (Dated: 12/04/2019)

## ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

## SECTION 9. Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	liquid
Colour	amber
Odour	characteristic
Odour threshold	Not available
pH	7-11
Melting point/ freezing point	Not available
Initial boiling point	245 °C
Boiling range	Not available
Flash point	~ 125 °C
Evaporation Rate	Not available
Flammability of solids and gases	not applicable
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1,020-1,070
Solubility	soluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	350 °C
Decomposition temperature	Not available
Viscosity	14,6 cSt (20 °C)
Explosive properties	Not available
Oxidising properties	Not available

### 9.2. Other information

VOC (Directive 2010/75/EC) :	0
VOC (volatile carbon) :	0

## SECTION 10. Stability and reactivity



**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

Page n. 11/21

Replaced revision:3 (Dated: 12/04/2019)

#### 10.1. Reactivity

The product may react exothermically on contact with strong oxidising or reducing agents, strong acids or bases.

#### 10.2. Chemical stability

Excessively high temperatures can cause thermal decomposition.

Hygroscopic.

#### 10.3. Possibility of hazardous reactions

See paragraph 10.1.

2-(2-BUTOXYETHOXY)ETHANOL

May react with: oxidising substances. May form peroxides with: oxygen. Develops hydrogen on contact with: aluminium. May form explosive mixtures with: air.

DIETHYLENE GLYCOL MONOMETHYL ETHER

Reacts violently developing heat on contact with: alkaline metals, strong acids, strong oxidants, oleum. Fire hazard. Develops flammable gas on contact with: calcium hypochlorite. Develops hydrogen on contact with: aluminium.

#### 10.4. Conditions to avoid

Avoid overheating.

2-(2-BUTOXYETHOXY)ETHANOL

Avoid exposure to: air.

DIETHYLENE GLYCOL MONOMETHYL ETHER

Possibility of explosion with air due to production of peroxides.

#### 10.5. Incompatible materials

Oxidising or reducing agents. Strong acids or bases.

Reaction mass of 2-[2-(2-Butoxyethoxy)ethoxy]ethanol



**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

Page n. 12/21

Replaced revision:3 (Dated: 12/04/2019)

Avoid contact with: water.

2-(2-BUTOXYETHOXY)ETHANOL

Incompatible with: oxidising substances, strong acids, alkaline metals.

2,6-di-tert-butyl-p-cresol

Avoid contact with: oxidising agents.

#### **10.6. Hazardous decomposition products**

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

2-(2-BUTOXYETHOXY)ETHANOL

May develop: hydrogen.

DIETHYLENE GLYCOL MONOMETHYL ETHER

When heated to decomposition releases: harsh fumes, zinc alloys.

2,6-di-tert-butyl-p-cresol

In decomposition develops: carbon oxides.

## **SECTION 11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

#### **11.1. Information on toxicological effects**

##### Metabolism, toxicokinetics, mechanism of action and other information

Information not available



**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

Page n. 13/21

Replaced revision:3 (Dated: 12/04/2019)

Information on likely routes of exposure

2-(2-BUTOXYETHOXY)ETHANOL

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

2-(2-BUTOXYETHOXY)ETHANOL

May be absorbed by inhalation, ingestion and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapour pressure of the substance.

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:  
Not classified (no significant component)  
LD50 (Oral) of the mixture:  
>2000 mg/kg  
LD50 (Dermal) of the mixture:  
Not classified (no significant component)

2,6-di-tert-butyl-p-cresol

LD50 (Oral) > 2930 mg/kg dw

LD50 (Dermal) > 2000 mg/kg dw

TRIETHYLENE GLYCOL

LD50 (Oral) > 2000 mg/kg

LD50 (Dermal) 16 ml/kg

LC50 (Inhalation) > 5,2 mg/l

DI-ISOPROPANOLAMINE

LD50 (Oral) 6720 mg/kg



**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

Page n. 14/21

Replaced revision:3 (Dated: 12/04/2019)

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

Reaction mass of 2-[2-(2-Butoxyethoxy)ethoxy]ethanol

LD50 (Oral) 2630 mg/kg bw

LD50 (Dermal) 3540 mg/kg bw

DIETHYLENE GLYCOL

LD50 (Oral) 12565 mg/kg Rat

LD50 (Dermal) 11890 mg/kg Rabbit

DIETHYLENE GLYCOL MONOMETHYL ETHER

LD50 (Oral) 5500 mg/kg Rat

2-(2-BUTOXYETHOXY)ETHANOL

LD50 (Oral) 3384 mg/kg Rat

LD50 (Dermal) 2700 mg/kg Rabbit

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY



**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

Page n. 15/21

Replaced revision:3 (Dated: 12/04/2019)

Suspected of damaging the unborn child

#### STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

#### STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

#### ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

## SECTION 12. Ecological information

No specific data are available for this product. Handle it according to good working practices. Avoid littering. Do not contaminate soil and waterways. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation. Please take all the proper measures to reduce harmful effects on aquifers.

### 12.1. Toxicity

2,6-di-tert-butyl-p-cresol

EC50 - for Crustacea > 0,61 mg/l/48h

Chronic NOEC for Crustacea 0,316 mg/l

TRIETHYLENE GLYCOL

EC50 - for Crustacea > 10000 mg/l/48h

DI-ISOPROPANOLAMINE

LC50 - for Fish > 222,2 mg/l/96h

Reaction mass of 2-[2-(2-  
Butoxyethoxy)ethoxy]ethanol

LC50 - for Fish > 1800 mg/l/96h

EC50 - for Crustacea > 3200 mg/l/48h

EC50 - for Algae / Aquatic Plants 391 mg/l/72h

EC10 for Algae / Aquatic Plants 188 mg/l/72h

DIETHYLENE GLYCOL

LC50 - for Fish > 75 g/l



## 12.2. Persistence and degradability

2,6-di-tert-butyl-p-cresol  
NOT rapidly degradable

TRIETHYLENE GLYCOL  
Rapidly degradable

DI-ISOPROPANOLAMINE  
Rapidly degradable

Reaction mass of 2-[2-(2-  
Butoxyethoxy)ethoxy]ethanol  
Rapidly degradable

DIETHYLENE GLYCOL MONOMETHYL  
ETHER  
Solubility in water 1000 - 10000 mg/l  
Rapidly degradable

2-(2-BUTOXYETHOXY)ETHANOL  
Solubility in water 1000 - 10000 mg/l  
Rapidly degradable

## 12.3. Bioaccumulative potential

TRIETHYLENE GLYCOL  
Partition coefficient: n-octanol/water -1,75

Reaction mass of 2-[2-(2-  
Butoxyethoxy)ethoxy]ethanol  
Partition coefficient: n-octanol/water 0,44

DIETHYLENE GLYCOL MONOMETHYL  
ETHER  
Partition coefficient: n-octanol/water -0,47

2-(2-BUTOXYETHOXY)ETHANOL  
Partition coefficient: n-octanol/water 1

## 12.4. Mobility in soil





**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

Page n. 17/21

Replaced revision:3 (Dated: 12/04/2019)

TRIETHYLENE GLYCOL

Partition coefficient: soil/water

1

#### 12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

#### 12.6. Other adverse effects

Information not available

### SECTION 13. Disposal considerations

#### 13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

### SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

#### 14.1. UN number

Not applicable

#### 14.2. UN proper shipping name

Not applicable

#### 14.3. Transport hazard class(es)

Not applicable



**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

Page n. 18/21

Replaced revision:3 (Dated: 12/04/2019)

**14.4. Packing group**

Not applicable

**14.5. Environmental hazards**

Not applicable

**14.6. Special precautions for user**

Not applicable

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

Information not relevant

**SECTION 15. Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3

Contained substance

Point 55 2-(2-BUTOXYETHOXY)ETHANOL Reg. no.: 01-2119475104-44-xxxx

Point 54 DIETHYLENE GLYCOL MONOMETHYL ETHER Reg. no.: 01-2119475100-52-xxxx



**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

Page n. 19/21

Replaced revision:3 (Dated: 12/04/2019)

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

**15.2. Chemical safety assessment**

A chemical safety assessment has been performed for the following contained substances

Reaction mass of 2-[2-(2-Butoxyethoxy)ethoxy]ethanol

DIETHYLENE GLYCOL

DI-ISOPROPANOLAMINE

DIETHYLENE GLYCOL MONOMETHYL ETHER

2,6-di-tert-butyl-p-cresol

**SECTION 16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

**Repr. 2** Reproductive toxicity, category 2

**Acute Tox. 4** Acute toxicity, category 4



**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

Page n. 20/21

Replaced revision:3 (Dated: 12/04/2019)

<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Eye Irrit. 2</b>	Eye irritation, category 2
<b>Aquatic Chronic 1</b>	Hazardous to the aquatic environment, chronic toxicity, category 1
<b>H361d</b>	Suspected of damaging the unborn child.
<b>H302</b>	Harmful if swallowed.
<b>H318</b>	Causes serious eye damage.
<b>H319</b>	Causes serious eye irritation.
<b>H410</b>	Very toxic to aquatic life with long lasting effects.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
4. Regulation (EU) 2015/830 of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)



**VALEO SERVICE SAS  
MEAO**

Revision nr. 4

Dated 14/05/2019

Printed on 23/05/2019

**BRAKE FLUID DOT4  
(401702-402104-402106-402401-402402-402403-  
402404-402405)**

Page n. 21/21

Replaced revision:3 (Dated: 12/04/2019)

13. Regulation (EU) 2017/776 (X Atp. CLP)

- The MerckIndex. - 10th Edition

- Handling Chemical Safety

- INRS - Fiche Toxicologique (toxicological sheet)

- Patty - Industrial Hygiene and Toxicology

- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition

- IFA GESTIS website

- ECHA website

- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

msds for B2C.

Changes to previous review:

The following sections were modified:

03 / 10 / 11 / 12 / 15.