

Valeo ClimSpray

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)

SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : Valeo ClimSpray
715991-715992

1.2. Relevant identified uses of the substance or mixture and uses advised against

Interior purifier.

1.3. Details of the supplier of the safety data sheet

Registered company name : VALEO SERVICE SAS.
Address : 70, rue Pleyel.93285.SAINT DENIS Cedex.France.
Telephone : +33 (0)1 49 45 32 32. Fax : +33 (0)1 49 45 32 03.
Email : vsa.msdsflt.mailbox@valeo.com

1.4. Emergency telephone number : +33 (0)1 45 42 59 59.

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

Other emergency numbers

National Poisons Information Service of England: <http://npis.org> - NHS 111: dial 111 - National Poisons Information Centre of Ireland: 353 (1) 809 2166 - LUXEMBOURG : (+352) 8002 5500 - European Emergency Number Association (EENA) : 112

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aerosol, Category 2 (Aerosol 2, H223 - H229).

Eye irritation, Category 2 (Eye Irrit. 2, H319).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

The propellant gas is taken into account when determining the health and environmental classification of the mixture.

2.2. Label elements

Biocidal mixture (see section 15).

Mixture for aerosol application.

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS02



GHS07

Signal Word :

WARNING

Hazard statements :

H223

Flammable aerosol.

H229

Pressurised container: May burst if heated.

H319

Causes serious eye irritation.

H412

Harmful to aquatic life with long lasting effects.

Precautionary statements - General :

P102

Keep out of reach of children.

Precautionary statements - Prevention :

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211

Do not spray on an open flame or other ignition source.

P251

Do not pierce or burn, even after use.

P260

Do not breathe spray.

P264

Wash hands thoroughly after handling.

P273

Avoid release to the environment.

P280

Wear protective gloves/protective clothing/eye protection/face protection.

Valeo ClimSpray

Precautionary statements - Response :

P305 + P351 + P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313

If eye irritation persists: Get medical advice/attention.

Precautionary statements - Storage :

P410 + P412

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Precautionary statements - Disposal :

P501

Dispose of contents/container at a disposal facility in accordance with local regulations.

2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) \geq 0.1% published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances \geq 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS**3.2. Mixtures****Composition :**

Identification	(EC) 1272/2008	Note	%
CAS: 109-87-5 EC: 203-714-2 REACH: 01-2119664781-31 DIMETHOXYMETHANE	GHS02 Dgr Flam. Liq. 2, H225	[1]	50 \leq x % < 100
CAS: 64-17-5 EC: 200-578-6 REACH: 01-2119457610-43 ETHANOL	GHS07, GHS02 Dgr Flam. Liq. 2, H225 Eye Irrit. 2, H319	[1]	10 \leq x % < 25
CAS: 124-38-9 EC: 204-696-9 CARBON DIOXIDE	GHS04 Wng Press. Gas, H281	[1] [7]	2.5 \leq x % < 10
CAS: 68391-01-5 EC: 269-919-4 QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-18-ALKYLDIMETHYL, CHLORIDES	GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Skin Corr. 1B, H314 Aquatic Acute 1, H400 M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 10		0 \leq x % < 0.1
CAS: 85409-23-0 EC: 287-090-7 REACH: 01-2120771812-51 QUATERNARY AMMONIUM COMPOUNDS, C12-14-ALKYL[(ETHYLPHENYL)METHYL] DIMETHYL, CHLORIDES	GHS07, GHS05, GHS09 Dgr Acute Tox. 4, H302 Skin Corr. 1B, H314 STOT SE 3, H335 Aquatic Acute 1, H400 M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 10		0 \leq x % < 0.1

Specific concentration limits:

Identification	Specific concentration limits	ATE
CAS: 109-87-5 EC: 203-714-2 REACH: 01-2119664781-31 DIMETHOXYMETHANE		oral: ATE = 6423 mg/kg BW
CAS: 64-17-5 EC: 200-578-6 REACH: 01-2119457610-43 ETHANOL		inhalation: ATE = 51 mg/1 4h (vapours) oral: ATE = 10470 mg/kg BW

Valeo ClimSpray

CAS: 68391-01-5 EC: 269-919-4 QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-18-ALKYLDIMETHYL, CHLORIDES		oral: ATE = 344 mg/kg BW
CAS: 85409-23-0 EC: 287-090-7 REACH: 01-2120771812-51 QUATERNARY AMMONIUM COMPOUNDS, C12-14-ALKYL[(ETHYLPHENYL)METHYL] DIMETHYL, CHLORIDES		oral: ATE = 344 mg/kg BW

Information on ingredients :

(Full text of H-phrases: see section 16)

[1] Substance for which maximum workplace exposure limits are available.

[7] Propellant gas

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. description of first aid measures**In the event of exposure by inhalation :**

If inhaled, move the patient into the fresh air and keep warm and at rest.

If breathing is irregular or has stopped, proceed with artificial respiration and seek medical attention.

In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

If there is any redness, pain or visual impairment, consult an ophthalmologist.

In the event of swallowing :

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

5.1. Extinguishing media

Keep packages near the fire cool, to prevent pressurised containers from bursting.

Suitable methods of extinction

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon

Prevent the effluent of fire-fighting measures from entering drains or waterways.

Unsuitable methods of extinction

In the event of a fire, do not use :

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

Valeo ClimSpray

5.3. Advice for firefighters

Due to the toxicity of the gas emitted on thermal decomposition of the products, fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures

Use drums to dispose of collected waste in compliance with current regulations (see section 13).

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

Remove contaminated clothing and protective equipment before entering eating areas.

To be translated (XML)

Fire prevention :

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn, even after use.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

Recommended equipment and procedures :

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Do not breathe in aerosols.

Avoid eye contact with this mixture.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.

Never open the packages under pressure.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Valeo ClimSpray

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters****Occupational exposure limits :**

- European Union (2022/431, 2019/1831, 2017/2398, 2017/164, 2009/161, 2006/15/CE, 2000/39/CE, 98/24/CE) :

CAS	VME-mg/m ³ :	VME-ppm :	VLE-mg/m ³ :	VLE-ppm :	Notes :
124-38-9	9000	5000	-	-	-

- ACGIH TLV (American Conference of Governmental Industrial Hygienists, Threshold Limit Values, 2010) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
109-87-5	1000 ppm				
64-17-5		1000 ppm		A3	
124-38-9	5000 ppm	30.000 ppm			

- Germany - AGW (BAuA - TRGS 900, 02/2022) :

CAS	VME :	VME :	Excess	Notes
109-87-5		500 ppm 1600 mg/m ³		2(II)
64-17-5		200 ppm 380 mg/m ³		4(II)
124-38-9		5000 ppm 9100 mg/m ³		2(II)

- Australia (NOHSC: 3008, 1995) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
109-87-5	1000 ppm 3110 mg/m ³			H	
64-17-5	1000 ppm 1880 mg/m ³			H	
124-38-9	12500 ppm 22500 mg/m ³	30000 ppm 54000 mg/m ³		A*	

- Austria (BGBl. II Nr. 156/2021) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
109-87-5	1000 ppm 3100 mg/m ³				
64-17-5	1000 ppm 1900 mg/m ³	2000 ppm 3800 mg/m ³			
124-38-9	5000 ppm 9000 mg/m ³	10000 ppm 18000 mg/m ³			

- Belgium (Royal decree of 11/05/2021) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
109-87-5	1000 ppm 3155 mg/m ³				
64-17-5	1000 ppm 1907 mg/m ³				
124-38-9	5000 ppm 9131 mg/m ³	30000 ppm 54784 mg/m ³		A	

- France (INRS - Outils 65 / 2021-1849, 2021-1763, decree of 09/12/2021) :

CAS	VME-ppm :	VME-mg/m ³ :	VLE-ppm :	VLE-mg/m ³ :	Notes :	TMP No :
109-87-5	1000	3100	-	-	-	84
64-17-5	1000	1900	5000	9500	-	84
124-38-9	5000	9000	-	-	-	-

Valeo ClimSpray

- Switzerland (Suva 2021) :

CAS	VME	VLE	Valeur plafond	Notations
109-87-5	1000 ppm 3100 mg/m ³	2000 ppm 6200 mg/m ³		
64-17-5	500 ppm 960 mg/m ³	1000 ppm 1920 mg/m ³		
124-38-9	5000 ppm 9000 mg/m ³			

- UK / WEL (Workplace exposure limits, EH40/2005, Fourth Edition 2020) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
109-87-5	1000 ppm 3160 mg/m ³	1250 ppm 3950 mg/m ³			
64-17-5	1000 ppm 1920 mg/m ³				
124-38-9	5000 ppm 9150 mg/m ³	15000 ppm 27400 mg/m ³			

- USA / OSHA PEL (Occupational Safety and Health Administration, Permissible Exposure Limits) :

CAS	TWA :	STEL :	Ceiling :	Definition :	Criteria :
109-87-5	1000 ppm 3100 mg/m ³				
64-17-5	1000 ppm 1900 mg/m ³				
124-38-9	5000 ppm 9000 mg/m ³				

8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles with protective sides accordance with standard EN166.

In the event of high danger, protect the face with a face shield.

Prescription glasses are not considered as protection.

Individuals wearing contact lenses should wear prescription glasses during work where they may be exposed to irritant vapours.

Provide eyewash stations in facilities where the product is handled constantly.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- PVA (Polyvinyl alcohol)

- Body protection

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Physical state

Physical state : Fluid liquid.

Colour

Unspecified

Valeo ClimSpray

Odour

Odour threshold : Not stated.

Freezing point

Freezing point / Freezing range : Not stated.

Boiling point or initial boiling point and boiling range

Boiling point/boiling range : Not relevant.

Flammability

Flammability (solid, gas) : Not stated.

Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) : Not stated.

Explosive properties, upper explosivity limit (%) : Not stated.

Flash point

Flash point interval : Not relevant.

Point/flash point interval: $\leq 21^{\circ}\text{C}$.**Auto-ignition temperature**

Self-ignition temperature : Not relevant.

Decomposition temperature

Decomposition point/decomposition range : Not relevant.

pH

pH (aqueous solution) : Not stated.

pH : Not relevant.

Kinematic viscosity

Viscosity : Not stated.

Solubility

Water solubility : Soluble.

Fat solubility : Not stated.

Partition coefficient n-octanol/water (log value)

Partition coefficient: n-octanol/water : Not stated.

Vapour pressure

Vapour pressure (50°C) : Below 110 kPa (1.10 bar).

Density and/or relative densityDensity : < 1 **Relative vapour density**

Vapour density : Not stated.

9.2. Other information

No data available.

9.2.1. Information with regard to physical hazard classes

No data available.

AerosolsChemical combustion heat : ≥ 20 kJ/g.Inflammation distance : < 75 cm.**9.2.2. Other safety characteristics**

No data available.

SECTION 10 : STABILITY AND REACTIVITY**10.1. Reactivity**

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

Valeo ClimSpray

10.4. Conditions to avoid

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- heating
- heat

10.5. Incompatible materials

Keep away from :

- acids
- oxidising agents

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

SECTION 11 : TOXICOLOGICAL INFORMATION**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

May have reversible effects on the eyes, such as eye irritation which is totally reversible by the end of observation at 21 days.

Splashes in the eyes may cause irritation and reversible damage

11.1.1. Substances**Acute toxicity :**

QUATERNARY AMMONIUM COMPOUNDS, C12-14-ALKYL[(ETHYLPHENYL)METHYL]DIMETHYL, CHLORIDES (CAS: 85409-23-0)

Oral route : LD50 = 344 mg/kg
Species : Rat

Dermal route : LD50 > 3000 mg/kg
Species : Rabbit

QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-18-ALKYLDIMETHYL, CHLORIDES (CAS: 68391-01-5)

Oral route : LD50 = 344 mg/kg
Species : Rat

Dermal route : LD50 > 3000 mg/kg
Species : Rabbit

ETHANOL (CAS: 64-17-5)

Oral route : LD50 = 10470 mg/kg
Species : Rat
OECD Guideline 401 (Acute Oral Toxicity)

Dermal route : 2,000 < LD50 <= 5000 mg/kg
Species : Rabbit
OECD Guideline 402 (Acute Dermal Toxicity)

Inhalation route (Vapours) : LC50 = 51 mg/l
Species : Rat
OECD Guideline 403 (Acute Inhalation Toxicity)
Duration of exposure : 4 h

DIMETHOXYMETHANE (CAS: 109-87-5)

Oral route : LD50 = 6423 mg/kg
Species : Rat

Valeo ClimSpray

Dermal route : LD50 > 5000 mg/kg
Species : Rabbit

Serious damage to eyes/eye irritation :

ETHANOL (CAS: 64-17-5)

Causes serious eye irritation.

Corneal haze :

1 <= Average score < 2 and effects totally reversible within 21 days of observation

Conjunctival redness :

2 <= Average score < 2.5 and effects totally reversible within 21 days of observation

11.1.2. Mixture

No toxicological data available for the mixture.

11.2. Information on other hazards**Monograph(s) from the IARC (International Agency for Research on Cancer) :**

CAS 67-63-0 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

CAS 91-64-5 : IARC Group 3 : The agent is not classifiable as to its carcinogenicity to humans.

CAS 64-17-5 : IARC Group 1 : The agent is carcinogenic to humans.

SECTION 12 : ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity**12.1.1. Substances**

QUATERNARY AMMONIUM COMPOUNDS, C12-14-ALKYL[(ETHYLPHENYL)METHYL]DIMETHYL, CHLORIDES (CAS: 85409-23-0)

Crustacean toxicity :

EC50 = 0.016 mg/l

Factor M = 10

Duration of exposure : 48 h

Algae toxicity :

0.001 < NOEC <= 0.01 mg/l

Factor M = 10

QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-18-ALKYLDIMETHYL, CHLORIDES (CAS: 68391-01-5)

Crustacean toxicity :

EC50 = 0.016 mg/l

Factor M = 10

Duration of exposure : 48 h

Algae toxicity :

0.001 < NOEC <= 0.01 mg/l

Factor M = 10

ETHANOL (CAS: 64-17-5)

Fish toxicity :

LC50 = 13000 mg/l

Species : Oncorhynchus mykiss

Duration of exposure : 96 h

NOEC = 245 mg/l

Crustacean toxicity :

EC50 = 858 mg/l

Species : Artemia salina

Duration of exposure : 24 h

OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

NOEC = 9.6 mg/l

Species : Ceriodaphnia dubia

Algae toxicity :

ECr50 = 275 mg/l

Species : Chlorella vulgaris

Duration of exposure : 72 h

Valeo ClimSpray

OECD Guideline 201 (Alga, Growth Inhibition Test)

EC10 mg/l
Species : *Chlorella vulgaris*
Duration of exposure : 72 h

DIMETHOXYMETHANE (CAS: 109-87-5)

Fish toxicity :

LC50 > 1000 mg/l
Duration of exposure : 96 h

Crustacean toxicity :

EC50 > 1200 mg/l
Species : *Daphnia magna*
Duration of exposure : 48 h**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability**12.2.1. Substances**

QUATERNARY AMMONIUM COMPOUNDS, C12-14-ALKYL[(ETHYLPHENYL)METHYL]DIMETHYL, CHLORIDES (CAS: 85409-23-0)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-18-ALKYLDIMETHYL, CHLORIDES (CAS: 68391-01-5)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

ETHANOL (CAS: 64-17-5)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

DIMETHOXYMETHANE (CAS: 109-87-5)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential**12.3.1. Substances**

ETHANOL (CAS: 64-17-5)

Octanol/water partition coefficient : log K_{ow} = -0.3

Bioaccumulation : BCF = 0.66

DIMETHOXYMETHANE (CAS: 109-87-5)

Octanol/water partition coefficient : log K_{ow} = 0**12.4. Mobility in soil**

No data available.

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Endocrine disrupting properties

No data available.

12.7. Other adverse effects

No data available.

German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :

WGK 2 : Hazardous for water.

Valeo ClimSpray

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2021 - IMDG 2020 [40-20] - ICAO/IATA 2022 [63]).

14.1. UN number or ID number

1950

14.2. UN proper shipping name

UN1950=AEROSOLS, flammable

14.3. Transport hazard class(es)

- Classification :



2.1

14.4. Packing group

-

14.5. Environmental hazards

-

14.6. Special precautions for user

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	2	5F	-	2.1	-	1 L	190 327 344 625	E0	2	D

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ	Stowage Handling	Segregation
	2	See SP63	-	See SP277	F-D. S-U	63 190 277 327 344 381 959	E0	- SW1 SW22	SG69

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	2.1	-	-	203	75 kg	203	150 kg	A145 A167 A802	E0
	2.1	-	-	Y203	30 kg G	-	-	A145 A167 A802	E0

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

Valeo ClimSpray

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

- Container information:

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH): <https://echa.europa.eu/substances-restricted-under-reach>.

- Particular provisions :

No data available.

- Labelling for biocidal products (Regulation (UE) n° 528/2012) :

Name	CAS	%	Product-type
QUATERNARY AMMONIUM COMPOUNDS, BENZYL-C12-18-ALKYLDIMETHYL, CHLORIDES	68391-01-5	0.46 g/kg	02
QUATERNARY AMMONIUM COMPOUNDS, C12-14-ALKYL[(ETHYLPHENYL)METHYL] DIMETHYL, CHLORIDES	85409-23-0	0.46 g/kg	02

Product-type 2 : Disinfectants and algacides not intended for direct application to humans or animals.

- German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :

WGK 2 : Hazardous for water.

- Swiss ordinance on the incentive tax on volatile organic compounds :

64-17-5 éthanol, seulement s'il s'agit d'alcools impropres à la consommation (art. 31 de la loi fédérale sur l'alcool)
67-63-0 propane-2-ol (alcool isopropylique)

15.2. Chemical safety assessment

No data available.

SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H225	Highly flammable liquid and vapour.
H281	Contains refrigerated gas; may cause cryogenic burns or injury.
H302	Harmful if swallowed.
H314	Causes severe skin burns and eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Abbreviations :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.
LC50 : The concentration of a test substance resulting in 50% lethality in a given period.
EC50 : The effective concentration of substance that causes 50% of the maximum response.
ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.
NOEC : The concentration with no observed effect.
REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.
ATE : Acute Toxicity Estimate
BW : Body Weight
STEL : Short-term exposure limit
TWA : Time Weighted Averages
TMP : French Occupational Illness table
TLV : Threshold Limit Value (exposure)

Valeo ClimSpray

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.